



Philips Ultinon Drive
5002C
3 inch cube pod light -
Driving

Sturdy one-piece body

IP69K waterproof
Corrosion-free stainless steel
Trouble-free operation

LUMUD5002CX1

Brilliant LED lighting for off-road adventures

Bright, long beam for superior visibility

For drivers who demand the maximum of themselves and their machines, we offer Philips Ultinon Drive 5000 series LED pod lights. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced LED pod lights can light the way.

Unmatched brightness for Off-road auxiliary lights

- Offering a mid-day color temperature up to 6500K

Powerful brightness, Rugged performance

- Bright, long beam for superior visibility

Easy Installation

- Trouble-free operation

Built for off road abuse

- Corrosion-free, stainless-steel mounting brackets

Waterproof & durable for challenging conditions

- IP69K waterproof to master the elements

PHILIPS

3 inch cube pod light - Driving
Sturdy one-piece body IP69K waterproof, Corrosion-free stainless steel, Trouble-free operation

LUMUD5002CX1/50

Specifications

Product description

- Break resistance
- Corrosion-free brackets: Yes, included
- ECE R10
- ECE R149: No
- ECE reference number: No
- Heat sink
- Impact protection rating (IK): IK07
- Ingress protection rating (IP): IP68 & IP69K
- Installation angle: 360°
- Material: Aluminum die-cast
- Number of LED's: 4x 7W
- Offroad boost: No
- One-piece body design
- Operating temperature: -40° F to 80° F
- Plug type: Connector with 0.5m cable
- Scratch resistant lens
- Storage Temperature: -40° F to 80° F
- Technology: LED
- Accessories (optional): additional brackets

Light characteristics

- Color temperature: 6000 K
- Beam length 1 lux: 482 ft.
- Beam length 1 lux (boost): N/A
- Beam length 3 lux: 275 ft.
- Beam length 3 lux (boost): N/A
- Beam width 1 lux: 210 ft.

- Beam width 3 lux: 164 ft.
- Light output (effective lumen): 2500
- Light output in Boost mode: N/A
- Beam pattern: Combo / Driving

Electrical characteristics

- Voltage: 9-48 Volt DC

Ordering information

- Order entry: UD5002CX1
- GOC: 78004037

Packaging Data

- EAN1: 046678004032
- EAN3: 50046678004037

Packed product information

- Width: 2.61 in.
- Height: 2.99 in.
- Gross weight box: 1.50 lb.
- Net weight product: 1.30 lb.
- Length: 2.99 in.
- MOQ (for professionals): 8

Outerpack information

- Length [in]: 5.91 in.
- Width [in]: 4.41 in.
- Height [in]: 3.46 in.

Highlights

Unsurpassed illumination

Offering a mid-day color temperature up to 6500K

Superior visibility

Up to 482 feet of down road and up to 209 feet in width make this a powerful addition to your high beam headlights.

Corrosion-free brackets

Corrosion-free, stainless-steel mounting brackets

Waterproof for durable light

IP69K waterproof to master the elements

Trouble-free

Trouble-free operation



Issue date 2024-10-12

Version: 1.0.2

UPC: 0 46678 00403 2

© 2024 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com