

# Product Environmental Profile

**Power Logic™**  
**ION7400 Panel Mount Utility Meter**



# Product Environmental Profile – PEP

## Product overview

The main purpose of the ION7400 meter is Class 0.2s power and energy metering. The meter is a performance measuring and monitoring device PMD/[SD|SS]/K70/0.2 per IEC 61557-12.

The functional unit is to analyze voltage and current in the ranges of 90-415V at 50/60Hz < 36VA, 90-120V at 400Hz < 28VA, 120-300V at 17W, and 1A (0.5s) and 5A (0.2s) during 10 years and a 100% use rate, in accordance with the relevant standards.

This range consists of the ION7400 meters.


The representative product used for the analysis is METSEION7400.

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.

The environmental analysis was performed in conformity with ISO 14040.

## Constituent materials

The mass of the product range is from 965 g and 985 g including packaging. It is 973 g for the METSEION7400. The constituent materials are distributed as follows:



## Substance assessment

Products of this range are designed in conformity with the requirements of the European RoHS Directive 2011/65/EU and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) . (<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page> )

## Product Environmental Profile – PEP

### Manufacturing

The ION7400 product range is manufactured at a Schneider Electric production site on which an ISO14001 certified environmental management system has been established.

### Distribution

The weight and volume of the packaging have been optimized, based on the European Union's packaging directive.

The ION7400 packaging weight is 267 g. It consists of cardboard, paper and polyethylene..

### Use

The products of the ION7400 range do not generate environmental pollution (noise, emissions) requiring special precautionary measures in standard use.

The electrical power consumption depends on the conditions under which the product is implemented and used. The duration of operating modes and the associated power consumption is summarized below:

| Phase   | Consumption (W) | Time % |
|---------|-----------------|--------|
| Active  | 20              | 10.00% |
| Standby | 7               | 85.00% |
| Sleep   | 0               | 0.00%  |
| OFF     | 0               | 5.00%  |

The product range does not require special maintenance operations.

### End of life

At end of life, the products in the ION7400 range have been optimized to decrease the amount of waste and allow recovery of the product components and materials.

This product range contains a PCB board with its components and a battery that should be separated from the stream of waste so as to optimize end-of-life treatment by special treatments. The location of these components and other recommendations are given in the End of Life Instruction document which is available for this product range on the Schneider-Electric Green Premium website [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) (<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>).

The recyclability potential of the products has been evaluated using the “ECO DEEE recyclability and recoverability calculation method” (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

According to this method, the potential recyclability ratio without packaging is: 51%.

As described in the recyclability calculation method this ratio includes only metals and plastics which have proven industrial recycling processes.

### Environmental impacts

Life cycle assessment has been performed on the following life cycle phases: Materials and Manufacturing (M), Distribution (D), Installation (I) Use (U), and End of life (E).

Modeling hypothesis and method:

- The calculation was performed on METSEION7400.
- Product packaging is included.
- Installation components: no special components included.
- Scenario for the Use phase: this product range is included in the category **Energy Consuming Product**. Assumed service lifetime is 10 years and use scenario: consumed power is 20W at in active mode at 10% operational time; consumed power 7W in standby mode at 85% operational time.

## Product Environmental Profile – PEP

- The geographical representative area for the assessment is Europe and the electrical power model used for calculation is European model.
- End of life impacts are based on a worst case transport distance to the recycling plant (1000km)

### Presentation of the product environmental impacts

| Environmental indicators                      | Unit                                | For give the name and commercial reference or description of the representative product |            |            |            |            |            |
|-----------------------------------------------|-------------------------------------|-----------------------------------------------------------------------------------------|------------|------------|------------|------------|------------|
|                                               |                                     | S = M + D + I + U + E                                                                   | M          | D          | I          | U          | E          |
| Air Acidification (AA)                        | g H+ eq                             | 1.1171E-01                                                                              | 1.3364E-02 | 4.2560E-05 | 0.0000E+00 | 9.8140E-02 | 1.6839E-04 |
| Air toxicity (AT)                             | m³                                  | 1.3312E+08                                                                              | 1.6319E+07 | 6.4450E+04 | 0.0000E+00 | 1.1647E+08 | 2.6642E+05 |
| Energy Depletion (ED)                         | MJ                                  | 9.0253E+03                                                                              | 1.0553E+03 | 1.6400E+00 | 0.0000E+00 | 7.9494E+03 | 1.8890E+01 |
| Global Warming Potential (GWP)                | g CO <sub>2</sub> eq.               | 5.7321E+02                                                                              | 6.5137E+01 | 2.1402E-01 | 0.0000E+00 | 5.0633E+02 | 1.5248E+00 |
| Hazardous Waste Production (HWP)              | kg                                  | 1.2764E+01                                                                              | 1.6153E+00 | 4.9985E-05 | 0.0000E+00 | 1.1148E+01 | 1.1286E-03 |
| Ozone Depletion Potential (ODP)               | g CFC-11 eq.                        | 2.7783E-05                                                                              | 6.3578E-06 | 9.0396E-08 | 0.0000E+00 | 2.0338E-05 | 9.9737E-07 |
| Photochemical Ozone Creation Potential (POCP) | g C <sub>2</sub> H <sub>4</sub> eq. | 1.2838E-01                                                                              | 1.7232E-02 | 1.6399E-04 | 0.0000E+00 | 1.0924E-01 | 1.7417E-03 |
| Raw Material Depletion (RMD)                  | Y-1                                 | 1.0104E-13                                                                              | 9.4317E-14 | 4.0026E-18 | 0.0000E+00 | 6.6943E-15 | 2.5928E-17 |
| Water Depletion (WD)                          | dm3                                 | 1.7772E+03                                                                              | 8.9377E+02 | 2.1260E-01 | 0.0000E+00 | 8.8142E+02 | 1.8490E+00 |
| Water Eutrophication (WE)                     | g PO <sub>4</sub> <sup>3-</sup> eq. | 2.1104E-02                                                                              | 1.9828E-02 | 3.0518E-06 | 0.0000E+00 | 1.2260E-03 | 4.7018E-05 |
| Water Toxicity (WT)                           | m³                                  | 1.0983E+02                                                                              | 6.2890E+01 | 5.3100E-02 | 0.0000E+00 | 4.5073E+01 | 1.8113E+00 |

Life cycle assessment has been performed with the EIME software (Environmental Impact and Management Explorer), version 5 and with its database version 2013-02.

The **USE** phase is the life cycle phase which has the greatest impact on the majority of environmental indicators, except on the Raw Material Depletion (RMD), Water Eutrophication (WE) and Water Toxicity (WT) where the manufacturing phase is responsible for the major impacts.

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range: the environmental indicators (excluding the RMD, WE, and WT) of other products in this family may be proportional extrapolated by energy consumption values. The RMD, WE and WT impact categories may be proportionally extrapolated by weight.

## System approach

As the products of the range are designed in accordance with the European RoHS Directive 2011/65/EU, they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

## Glossary

|                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Air Acidification (AA)</b>             | The acid substances present in the atmosphere are carried by rain. A high level of acidity in the rain can cause damage to forests. The contribution of acidification is calculated using the acidification potentials of the substances concerned and is expressed in mole equivalent of H <sup>+</sup> .                                                                                                                                                                                       |
| <b>Air Toxicity (AT)</b>                  | This indicator represents the air toxicity in a human environment. It takes into account the usually accepted concentrations for several gases in the air and the quantity of gas released over the life cycle. The indication given corresponds to the air volume needed to dilute these gases down to acceptable concentrations.                                                                                                                                                               |
| <b>Energy Depletion (ED)</b>              | This indicator gives the quantity of energy consumed, whether it is from fossil, hydroelectric, nuclear or other sources. It takes into account the energy from the material produced during combustion. It is expressed in MJ.                                                                                                                                                                                                                                                                  |
| <b>Global Warming (GW)</b>                | The global warming of the planet is the result of the increase in the greenhouse effect due to the sunlight reflected by the earth's surface being absorbed by certain gases known as "greenhouse-effect" gases. The effect is quantified in gram equivalent of CO <sub>2</sub> .                                                                                                                                                                                                                |
| <b>Hazardous Waste Production (HWP)</b>   | This indicator quantifies the quantity of specially treated waste created during all the life cycle phases (manufacturing, distribution and utilization). For example, special industrial waste in the manufacturing phase, waste associated with the production of electrical power, etc. It is expressed in kg.                                                                                                                                                                                |
| <b>Ozone Depletion (OD)</b>               | This indicator defines the contribution to the phenomenon of the disappearance of the stratospheric ozone layer due to the emission of certain specific gases. The effect is expressed in gram equivalent of CFC-11.                                                                                                                                                                                                                                                                             |
| <b>Photochemical Ozone Creation (POC)</b> | This indicator quantifies the contribution to the "smog" phenomenon (the photochemical oxidation of certain gases which generates ozone) and is expressed in gram equivalent of ethylene (C <sub>2</sub> H <sub>4</sub> ).                                                                                                                                                                                                                                                                       |
| <b>Raw Material Depletion (RMD)</b>       | This indicator quantifies the consumption of raw materials during the life cycle of the product. It is expressed as the fraction of natural resources that disappear each year, with respect to all the annual reserves of the material.                                                                                                                                                                                                                                                         |
| <b>Water Depletion (WD)</b>               | This indicator calculates the volume of water consumed, including drinking water and water from industrial sources. It is expressed in dm <sup>3</sup> .                                                                                                                                                                                                                                                                                                                                         |
| <b>Water Eutrophication (WE)</b>          | Eutrophication is a natural process defined as the enrichment in mineral salts of marine or lake waters or a process accelerated by human intervention, defined as the enrichment in nutritive elements (phosphorous compounds, nitrogen compounds and organic matter). This indicator represents the water eutrophication of lakes and marine waters by the release of specific substances in the effluents. It is expressed in grams equivalency of PO <sub>4</sub> <sup>3-</sup> (phosphate). |
| <b>Water Toxicity (WT)</b>                | This indicator represents the water toxicity. It takes into account the usually accepted concentrations for several substances in water and the quantity of substances released over the life cycle. The indication given corresponds to the water volume needed to dilute these substances down to acceptable concentrations.                                                                                                                                                                   |

PEP achieved with Schneider-Electric TT01 V13 and TT02 V22 procedures in compliance with ISO14040 series standards

|                                                                                       |  |  |          |                                                                                           |                                                                                       |
|---------------------------------------------------------------------------------------|--|--|----------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Registration N° : <b>SCHN-2015-194</b>                                                |  |  |          | Applicable PCR : PEP-PCR-ed 2.1-EN-2012 12 11                                             |                                                                                       |
| Verifier accreditation N° : VH08                                                      |  |  |          | Program information: <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a> |                                                                                       |
| Date of issue: 12-2015                                                                |  |  |          | Period of validity: 4 years                                                               |                                                                                       |
| Independent verification of the declaration and data, according to ISO 14025:2006     |  |  |          |                                                                                           |                                                                                       |
| Internal                                                                              |  |  | External |                                                                                           | X                                                                                     |
| In compliance with ISO 14025:2006 type III environmental declarations                 |  |  |          |                                                                                           |  |
| PCR review was conducted by an expert panel chaired by J. Chevalier (CSTB).           |  |  |          |                                                                                           |                                                                                       |
| The elements of the actual PEP cannot be compared with elements from another program. |  |  |          |                                                                                           |                                                                                       |

### Schneider Electric Industries SAS

35, rue Joseph Monier  
CS 30323  
F- 92506 Rueil Malmaison Cedex  
RCS Nanterre 954 503 439  
Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)