

KVR100X72C2L/128

128MB PC100 CL2 168-Pin ECC

Low Profile SDRAM DIMM Module

DESCRIPTION:

This document describes ValueRAM's 16M x 72-bit (128MB), CAS Latency 2 (CL2) SDRAM (Synchronous DRAM) PC100 low profile memory module. The components on this module include eighteen 8M x 8-bit (2M x 8-bit x 4 Bank / PC100 components) SDRAM in TSOP packages. This 168-pin DIMM uses gold contact fingers and requires +3.3V. The electrical and mechanical specifications are as follows:

FEATURES:

- | | |
|--------------------------|---|
| ✓ CLK Cycle Time (tCC) | min. = 10ns (CAS Latency = 2) / max. = 1000ns |
| ✓ Row Cycle Time (tRC) | 70ns |
| ✓ CLK to Output (tSAC) | max. = 6ns (CAS Latency = 2) |
| ✓ Single Power Supply of | +3.3V (+/- .3V) |
| ✓ Power | 3.938 W (operating) |
| ✓ UL Rating | 94 V - 0 |

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.2" (30.48mm).




Figure 1: KVR100X72C2L/128 168-Pin SDRAM Module