

Xerox® VersaLink® C9000 Color Printer



The VersaLink C9000 Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK C9000DT
One-Sided Speed¹ 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in. / SRA3 / 320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm
Two-Sided Speed¹ 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in. / SRA3 / 320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm
Monthly Duty Cycle²	Up to 270,000 pages / month
Recommended Average Monthly Print Volume³	Up to 30,000 pages per month
Hard Drive	320 GB HDD
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

Xerox® VersaLink® C9000 Color Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V +/-10 % Frequency: 50/60 Hz +/-3 %, 12A			
Europe and Other Geographies	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 %, 10A			
POWER CONSUMPTION				
Printing ⁴	For 110V: 2.85 kWh For 220V: 2.82 kWh			
Standby Mode ⁴	110V: 75.3 Watts or less 220V: 73.8 Watts or less			
Sleep Mode ⁴	110V: 0.48 watts or less 220V: 0.53 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	Below 48° C, and in compliance with MN2-810.13			
Required Temperature Range (Operating)	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85 %			
Required Relative Humidity	15 % to 85 %; must be 62.5 % or below at 32° C			
Sound Power Levels	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.64 B(A) Standby: 3.38 B(A)			
Sound Pressure Levels	Printing: 58.2 dB or less Standby: 15.1 dB or less Full System (including finisher) Printing: 58.1 dB Standby: 15.3 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 16 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink C9000/DT	24.4 in. / 620 mm	28.5 in. / 723 mm	31.9 in. / 809.3 mm	178 lb. / 80.8 kg
Two Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	60.0 lb. / 27.2 kg
Tandem Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	74.5 lb. / 33.8 kg
High Capacity Feeder	15.3 in. / 389 mm	23.7 in. / 602.9 mm	15.0 in. / 380.01 mm	63.9 lb. / 29.0 kg
Office Finisher	22 in. / 559.8 mm	21.7 in. / 552 mm	39.8 in. / 1012 mm	61.7 lb. / 28.0 Kg
Booklet Maker (Office Finisher)	11.75 in. / 298.5 mm	23.5 in. / 597 mm	42.5 in. / 1080 mm	20.3 lb. / 9.2 Kg
BR Booklet Maker Finisher	30.28 in. / 769.2 mm	28.5 in. / 723 mm	41.5 in. / 1055.1 mm	134.3 lb. / 60.9 Kg

Xerox® VersaLink® C9000 Color Printer

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink C9000/DT	32.8 in. / 833 mm	28.2 in. / 717 mm	33.4 in. / 852 mm	209.4 lb. / 95 kg
High Capacity Feeder	20.7 in. / 526 mm	29.8 in. / 756 mm	19.3 in. / 491 mm	74.3 lb. / 33.7 kg
Two Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	72.7 lb. / 33 kg
Tandem Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	86 lb. / 39 kg
Office Finisher	27.2 in. / 690 mm	40.2 in. / 1021 mm	25.7 in. / 654 mm	82 lb. / 37 kg
Booklet Maker Finisher	20 in. / 507 mm	30 in. / 761 mm	17.2 in. / 437 mm	31 lb. / 14 kg
BR Booklet Maker Finisher	30 in. / 764 mm	30.5 in. / 774 mm	47.4 in. / 1203 mm	169.7 lb. / 77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in. / 533 mm	23.1 in. / 589 mm	12.6 in. / 319 mm	14.3 lb. / 6.5 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				
PRINT				
First-Print-Out Time	As fast as 10.5 seconds color			
	As fast as 10 seconds black			
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL			
Color Management	Embedded spot color table with the ability to swap out PANTONE® approved color table, Custom spot color editor, Xerox® Precise Color Management System software			
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper			

Xerox® VersaLink® C9000 Color Printer

Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® UNIX® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.
Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.

Xerox® VersaLink® C9000 Color Printer

Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
Mopria® Certified	ConnectKey Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android™) smartphone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
Xerox® Print Services plug-in for Android™	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security—for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow. • Xerox® Workplace Suite: On-site, your server • Xerox® Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.com/Mobility.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey Apps (Found at the Xerox® App Gallery App)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device.

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
ACCOUNTING	
XEROX® STANDARD ACCOUNTING / NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	- Enhanced network accounting with up to the minute data on how the system is being used - Comprehensive management and enterprise scale tracking and reporting of device print usage - Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com - Security enhancements include simultaneous support for HTTP/HTTPS protocols - Device requests account authentication from third party server enabling larger databases of users and accounts - Accept Authentication Login at control panel and pass to third party Networking Account
PAPER HANDLING	
BYPASS TRAY	
Capacity ⁵	100 sheets
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm
Weights	Simplex: 18 lb. bond to 130 lb. cover/64 to 350 gsm Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm

Xerox® VersaLink® C9000 Color Printer

Types	Bond Plain Paper Cardstock Custom Envelopes Extra Heavyweight Cardstock Extra Heavyweight Glossy Cardstock	Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Postcards Recycled
TRAY 1 AND 2			
Capacity⁵	520 sheets each		
Sizes	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
TWO TRAY MODULE			
Capacity⁵	1,040 sheets		
Sizes	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
TANDEM TRAY MODULE			
Capacity⁵	2,000 sheets		
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5		
Weights	18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
HIGH CAPACITY FEEDER			
Capacity⁵	2,000 sheets		
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5		
Weights	18 lb. bond to 95 lb. cover/64 to 216 gsm		
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled

Xerox® VersaLink® C9000 Color Printer

ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)	
Capacity⁵	Up to 50 envelopes
Sizes	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm
TOTAL CAPACITY	
VersaLink C9000/DT Capacity⁵	1,140 sheets
Maximum Capacity⁵	5,140 sheets
FINISHING	
OUTPUT TRAYS	
Catch Tray	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)
OFFICE FINISHER (OPTIONAL)	
Capacity⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in. / A4 to 11 x 17 in. / A3)
Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover/60 to 220 gsm
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm
Hole Punch (Optional) North America: Europe:	Up to 65 lb. cover (200 gsm) 2/3 hole punch 2/4 hole punch
BOOKLET MAKER FOR OFFICE FINISHER (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)	
Capacity⁵	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled / 60-105 gsm only
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)	
Capacity⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

Xerox® VersaLink® C9000 Color Printer

Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNMP, MDNS
REMOTE CONTROL PANEL	
	- Enables faster, more convenient technical support and user training - IT administrators and other authorized users can control the device remotely from a web page on any PC - Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB	
	- A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system - Works with any SNMP-managed printer from any manufacturer - Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	- Tray status/contents - Consumables status - Billing/Usage - Quick Links - Online Support
Print Queue Viewing	Job print queue management—view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Xerox® VersaLink® C9000 Color Printer

WHAT'S IN THE BOX		
	• VersaLink C9000 Color Printer • Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 12,000 print capacity⁶, Black: 18,000 print capacity⁶) • Drum Cartridge – One of each (Cyan, Magenta, Yellow, and Black 190,000 print capacity)⁶ • Quick Use Guide • Install Guide • Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide) • Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Cyan: 12,300 standard pages ⁵ Magenta: 12,300 standard pages ⁵ Yellow: 12,300 standard pages ⁵ Black: 18,900 standard pages ⁵	106R04062 106R04063 106R04064 106R04065
High Capacity Toner Cartridges	Cyan: 26,500 standard pages ⁶ Magenta: 26,500 standard pages ⁶ Yellow: 26,500 standard pages ⁶ Black: 31,400 standard pages ⁶	106R04074 106R04075 106R04076 106R04077
Drum Cartridge	Cyan: 190,000 standard pages ⁶ Magenta: 190,000 standard pages ⁶ Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶	101R00602
Waste Cartridge	47,000 standard pages ⁷	108R01504
IBT Cleaner	160,000 standard pages ⁷	104R00256
Transfer Roller	200,000 standard pages ⁷	116R00015
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Office Finisher (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177
ACCESSORIES / OPTIONS		
Two Tray Module		097S04969
Tandem Tray Module		097S04970
High Capacity Feeder		097S04845
Envelope Tray (Replaces Tray 1)		497K17880
Office Finisher (includes Gap Filler)		497K21010
2/3 Hole Punch for Office Finisher		497K03860
2/4 Hole Punch for Office Finisher		497K03870

Xerox® VersaLink® C9000 Color Printer

Booklet Maker for Office Finisher	497K03852
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker finisher with 2/4 Hole Punch	097S04982
Swedish 4 Hole Punch for BR Finisher	497K14370
Wireless Network Adapter Kit	497K16750
Xerox Precise Color Management System	097S04974
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb. 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/Latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.