



- ▶ 60" (152,5 CM) DISPLAY FOR 24/7 HIGH-BRIGHTNESS RETAIL SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 2000CD/M2
- ▶ LOCAL DIMMING
- ▶ BEZEL ONLY 19,8 MM
- ▶ 24/7 50.000 HOURS LIFE TIME MAX.
- ▶ 5.000:1 CONTRAST RATIO
- ▶ 5 X 5 MULTI-SCREEN CAPABILITY (ENLARGEMENT)
- ▶ MODULE SLOT SYSTEM

Sharp's large-format, high-performance and high-brightness LCD monitors are designed to meet the diverse needs of business users and boast solid reliability, superb durability, and easy operation. They come in a wide range of sizes with a choice of portrait or landscape installation, allowing customers to choose the monitor best suited to location and purpose. Not only are Sharp LCD monitors a dynamic and effective way to convey information, but they also add visual impact to offices and public spaces, with the added advantage of low power consumption. Also, Sharp's UV2A technology, found in the PN-A601, delivers extremely deep blacks and bright, vivid colours while offering additional energy savings through efficient use of light from the backlight. Just another reason why Sharp LCD monitors are such a dependable way to broaden business potential . . .

DISPLAY MODULE DATA

- ▶ Panel Technology: **UV2A, local dimming**
- ▶ Native Resolution (Pixels): **1,920 X 1,080**
- ▶ Diagonal Size (inches / cm): **60/152.5**
- ▶ Aspect Ratio: **16:9**
- ▶ Backlight Technology: **LED, Full Array**
- ▶ Brightness (cd/m2): **2000**
- ▶ Contrast Ratio: **1,000, 000: 1 (local dimming set to HIGH)5,000:1 (without local dimming)**
- ▶ Display Colours: **1.06b**
- ▶ Response Time (grey to grey avg) ms: **6**
- ▶ Viewing Angle (H/V)0 CR >10: **176/176**

POWER SUPPLY AND OPERATING ENVIRONMENT

- ▶ Operating Voltage(ACV) / Frequency(Hz): **100-240/50-60**
- ▶ Power Consumption (W) (Operating MAX): **620**
- ▶ Operating Temperature (oC): **0 - 40**
- ▶ Humidity (%): **20 - 80**
- ▶ Heat Dissipation (BTU/h) MAX: **2115,4**

WEIGHTS AND MEASURES

- ▶ Bezel Size (L/R) mm: **19.8**
- ▶ Bezel Size (U/L) mm: **19.8**
- ▶ Product Dimensions (W/H/D) mm: **1.374 x 793 x 147**
- ▶ Product Weight Without Stand (Kg): **45**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- ▶ HDMI: **1**
- ▶ DVI-D: **1 (OPT PN-ZB01)**
- ▶ VGA: **1**
- ▶ Component: **1 (OPT PN-ZB01)**
- ▶ Composite: **1 (OPT PN-ZB01)**
- ▶ S-Video: **1 (OPT PN-ZB01)**
- ▶ Audio 3.5mm Jack: **1**
- ▶ Audio RCA R-L: **2 (OPT PN-ZB01)**

CONNECTIVITY (CONTROL/SERIAL DATA)

- ▶ RS232C IN: **1**
- ▶ RS232C OUT: **1**
- ▶ LAN Port: **1 (OPT PN-ZB01)**

KEY SPECIFICATIONS

- ▶ 24/7 Operation Certified: ✓
- ▶ Local Dimming: ✓
- ▶ Built in Speakers (W): **10 x 10**
- ▶ Computer Input - Plug and Play: ✓
- ▶ Power Management: ✓
- ▶ Cabinet Colour: **BLACK**
- ▶ Brightness Sensor: ✓
- ▶ Daisychain (Mirror mode): ✓

SAFETY AND ENVIRONMENT (EUROPE)

- ▶ CE, CB Report: ✓
- ▶ Presence of Lead (Accepted application of RoHS Directive): ✓

INSTALLATION

- ▶ Landscape: ✓
- ▶ Portrait: ✓

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- ▶ DVI-D: **1 (OPT PN-ZB01)**
- ▶ Audio RCA R-L: **1**
- ▶ External Speaker: **10W+10W (OPT PN-ZB01)**

www.sharp.co.uk

SHARP
Be Original.

SHARP BUSINESS SYSTEMS UK PLC.
4 FURZEGROUND WAY
STOCKLEY PARK
UXBRIDGE, MIDDLESEX UB11 1EZ. TEL. 0208 734 2000