

Philips
Stereo dubbing cable

6 ft
3.5 mm (M) - 3.5 mm (M)

SWA2162W



Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality

- Nickel-plated connectors for reliable contact
- High purity copper conductor for reliable signal transfer

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket

Protects against signal loss

- Bare copper shielding

PHILIPS

Stereo dubbing cable
6 ft 3.5 mm (M) - 3.5 mm (M)

Specifications

Inner Carton

- Gross weight: 0.328 kg
- Gross weight: 0.723 lb
- GTIN: 2 06 09585 16308 3
- Inner carton (L x W x H): 8.1 x 5.1 x 3.7 inch
- Inner carton (L x W x H): 20.6 x 13.0 x 9.4 cm
- Nett weight: 0.240 kg
- Nett weight: 0.529 lb
- Number of consumer packagings: 6
- Tare weight: 0.088 kg
- Tare weight: 0.194 lb

Outer Carton

- Gross weight: 4.600 kg
- Gross weight: 10.141 lb
- GTIN: 1 06 09585 16308 6
- Outer carton (L x W x H): 16.9 x 16.1 x 8.3 inch
- Outer carton (L x W x H): 42.9 x 40.9 x 21.1 cm
- Nett weight: 2.880 kg

- Nett weight: 6.349 lb
- Number of consumer packagings: 72
- Tare weight: 1.720 kg
- Tare weight: 3.792 lb

Packaging dimensions

- Packaging dimensions (W x H x D):
7.1 x 19.8 x 2.5 cm
- Packaging dimensions (W x H x D):
2.8 x 7.8 x 1 inch
- Gross weight: 0.048 kg
- Gross weight: 0.106 lb
- Nett weight: 0.088 lb
- Nett weight: 0.040 kg
- Number of products included: 1
- Packaging type: Blister
- Tare weight: 0.018 lb
- Tare weight: 0.008 kg
- UPC: 6 09585 16308 9

SWA2162W/27

Highlights

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.



Issue date 2014-03-14

Version: 3.1.9

12 NC: 8670 000 47877
UPC: 6 09585 16308 9

© 2014 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com