

Reolink-Video-Doorbell-PoE-Specifications		
	Model	Reolink Video Doorbell PoE
Video & Audio	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	Default: 2560X1920 (5 megapixels) @20FPS
	Lens	f=2.26mm F=2.0, with IR cut
	Video Format	H.264
	Field of View	Horizontal: 134°
		Vertical: 97°
		Diagonal: 180°
	Pre-Motion Recording	Support
	Audio	Two-way audio, noise reduction, echo suppression
Power	Quick Replies	Support
	PoE	IEEE 802.3af, 48V Active
	Hardwired	12-24VAC 50/60Hz, 24VDC
Interfaces	Power	Power port
	System	Reset button
	Ethernet	One 10M/100Mbps RJ45
	Storage	Micro SD card slot (Max. 256GB), works with Reolink NVR
	Audio	Built-in 2 microphones & a speaker
Software	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)
		Substream: 4fps - 15fps (default: 10fps)
	Code Rate	Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)
		Substream: 64Kbps - 512Kbps (default: 256Kbps)
	Browsers Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/person detection; visit notification
	Recording Modes	Motion recording (default); 24/7 recording; scheduled recording
	Protocols & Standards	HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Working Environment	Work with	Google Assistant
	Temperature	Operating temperature: -10°C~+50°C (14°F~122°F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	Support
Size & Weight	Dimension	133mm(H) x 48mm(W) x 23mm(T)
	Weight	96g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .