

Product data sheet

Specifications



M8800C energy meter - 5 MB - flicker - 1 A input - 50 Hz - RS232/485+RS485

M8800C2E0B5A0A0A

Main

Range	PowerLogic
Device short name	ION8800C
Product or component type	Energy and power quality meter

Complementary

Power quality analysis	symmetrical component voltage sag and swell detection programmability (logic and math functions) up to the 63rd harmonic
Device application	Instrument transformer correction Equipment monitoring and control Demand and power factor control Energy pulsing and totalisation Contract optimisation Load curtailment Power monitoring Tariff metering Co-generation and IPP monitoring
Type of measurement	Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power per phase Reactive power total Reactive power per phase
Supply voltage	85...240 V AC 47...63 Hz 110...270 V DC
Network frequency	50 Hz
[In] rated current	1 A
Type of network	1P + N 3P 3P + N
Power consumption in VA	19 VA
Maximum power consumption in VA	32 VA
Display type	FSTN transfective LCD
Sampling rate	1024 samples/cycle
Measurement current	0...1 A
Input type	Current 0.001...10 A (impedance 0.01 Ohm)

Measurement voltage	57...288 V AC phase to neutral 99...500 V AC phase to phase
Frequency measurement range	47...63 Hz
Number of inputs	0
Measurement accuracy	Current 0.1 % Voltage 0.1 % Power 0.2 % Power factor 0.1 % Frequency 0.005 Hz Energy 0.2 %
Accuracy class	Class 0.2S active energy conforming to IEC 62053-22 Class 0.2S reactive energy conforming to IEC 62053-23
Number of outputs	1 alarm output 8 form A triac output 4 form C solid state output 2 IEC 1107 pulse
Communication port protocol	DLMS ION DNP3 Modbus RTU, master/slave at <= 19200 bauds Modbus RTU, master/slave at 300...57600 bauds Modbus RTU, master/slave at 300...115200 bauds IEC 1107 at <= 19200 bauds
Communication port support	Screw terminal block: RS485 Infrared DB9: RS485/RS232
Data recording	Min/max of instantaneous values Waveform logs Data logs GPS synchronisation Alarms Transient logs Historical logs Time stamping
Transmission rate	<= 19200 bauds 300...57600 bauds 300...115200 bauds
Memory capacity	5 MB
Web services	Web server
Tamperproof of settings	Protected by access code
Compatibility code	ION8800C

Environment

Electromagnetic compatibility	Conducted RF disturbances conforming to IEC 61000-4-6 Immunity to impulse waves conforming to IEC 61000-4-12 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Electrostatic discharge conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted and radiated emissions B conforming to CISPR 22
Mounting mode	Rack-mounted
Enclosure type	19" rack
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP51 conforming to IEC 60529
Relative humidity	5...95 %
Pollution degree	2
Ambient air temperature for operation	-10...45 °C
Ambient air temperature for storage	-25...70 °C
Operating altitude	0...2000 m

Product certifications	EGR ESKOM GOST NMI
Standards	IEC 62052-11 IEC 60950
Width	202.1 mm
Depth	261.51 mm
Height	132.2 mm
Product weight	6 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.0 cm
Package 1 Width	53.0 cm
Package 1 Length	44.0 cm
Package 1 Weight	7.0 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)