

PHILIPS

7 inch Round
Driving Light

Ultinon Drive 5011R


Sturdy one-piece body

IP69K waterproof

Corrosion-free stainless steel

Trouble-free operation

LUMUD5011RX1



Brilliant LED lighting for off-road adventures

Bright, long beam for superior visibility

For drivers who demand the maximum of themselves and their machines, we offer Philips Ultinon Drive 5000 series LED driving lights. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced.

Powerful brightness, Rugged performance

- Bright, long beam for superior visibility

Off-road auxiliary lights

- Offering a mid-day color temperature up to 6500K

Durable equipment for challenging conditions

- Corrosion-free, stainless-steel mounting brackets
- IP69K waterproof to master the elements

Easy installation

- Trouble-free operation

Highlights

Superior visibility

Up to 1279 feet of down road and up to 131 feet in width make this a powerful addition to your high beam headlights.

Unsurpassed illumination

High Power LEDs offer 4200 effective lumens with up to 6500K bright white light.

Corrosion-free brackets

Thick Aluminum faceplate, stainless steel brackets help achieve an IK07 shock protection rating.

Waterproof for durable light

Tested for close range high pressure, high temperature water rated IP68 and IP69K.

Trouble-free

Mount and connect to battery using our wiring harnesses UD1005W or UD1006W, sold separately.

Specifications

Electrical characteristics

Voltage: 9-30 Volt DC

Light characteristics

Beam length 1 lux: 1280 ft.

Beam length 1 lux (boost): N/A

Beam length 3 lux: 574 ft.

Beam length 3 lux (boost): N/A

Beam width 1 lux: 131 ft.

Beam width 3 lux: 82 ft.

Color temperature: 6500 K K

Light output (effective lumen): 4200

Light output in Boost mode: N/A

Ordering information

GOC: 78004099

Order entry: UD5011RX1

Outerpack information

Height [in]: 8.66 in.

Length [in]: 8.66 in.

Width [in]: 7.87 in.

Packaging Data

EAN1: 046678004094

EAN3: 50046678004099

Packed product information

Gross weight box: 3.96 lb.

Height: 7.09 in. cm

Length: 7.87 in.

Net weight product: 3.40 lb.

MOQ (for professionals): 2

Width: 3.08 in. cm

Product description

Accessories (optional): Additional brackets

Break resistance

Corrosion-free brackets: Yes, included

ECE R10: No

ECE R149: No

ECE reference number: No

Heat sink: N/A

Impact protection rating (IK): IK07

Ingress protection rating (IP): IP68 & IP69K

Installation angle: 360°

Material: Aluminum die-cast

Number of LED's: 21x 5W

Offroad boost: No

One-piece body design

Operating temperature: -40° F to 176° F

Plug type: Connector with 0.5m cable

Scratch resistant lens

Storage Temperature: -40° F to 176° F

Technology: LED

