

PHILIPS

10 Inch Single Row
LED Lightbar Yellow

Ultinon Drive 5011LY

Sturdy one-piece body

IP69K waterproof

Corrosion-free stainless steel

Trouble-free operation

UD5011LYX1



Superior for driving during fog, rain, and snow

Enhanced visibility

For those who drive in hazardous conditions, we offer Philips Ultinon Drive 5000 series selective yellow LED lightbars. These lightbars provide a better option for penetrating through snow, fog, rain, or other low visibility conditions.

Enhanced visibility, Powerful Performance

- Bright, long beam for superior visibility

Durable equipment for challenging conditions

- IP69K waterproof to master the elements
- Corrosion-free, stainless-steel mounting brackets

Off-road auxiliary lights

- See further in hazardous weather conditions

Simple installation

- Trouble-free operation

Ultinon Drive 5011LY

10 Inch Single Row LED Lightbar Yellow

LUMUD5011LYX1/50

Highlights

Waterproof for durable light

With its ingenious screwless design, Ultinon Drive 5000 series lightbars are rated IP68 and IP69K. The IP69K rating is essential as it provides the highest level of protection against dust, high temperature, and high pressure water. The IP69K rating also ensures product safety as well as reduces maintenance and future replacement costs. These superior ratings also protect your lightbars when using a power washer or any other rigorous cleaning processes.

Trouble-free

Ultinon Drive 5000 series lightbars are designed and tested to ensure they will function smoothly with your vehicles electrical systems. The Ultinon Drive 5000 series 10 inch single row LED lightbar can easily connect to your battery using our single lamp wiring harness (UD1005W) or dual lamp wiring harness (UD1006W), sold separately.

Superior visibility

Ultinon Drive 5000 series lightbars provide outstanding beam performance with brilliant illumination that extends up to 1,050 feet. With high lumen output coming from the powerful LEDs, the Ultinon Drive series provides ample

visibility for faster reaction time during inclement weather conditions. A color temperature of 3000K emits a selective yellow light that is excellent for penetrating fog, rain and snow.

Superior visibility

Ultinon Drive 5000 series selective yellow lightbars provide many advantages when off-roading during extreme weather elements. The 3000K selective yellow light cuts through fog, dust, and other atmospheric conditions that reduce visibility much easier than the other higher rated color temperatures. The 3000K selective yellow light provides less glare than other colors of lights, making it much easier to see obstacles in your path as well as provides a more natural and comfortable color, reducing eye strain during your adventure.

Corrosion-free brackets

Ultinon Drive 5000 series mounting brackets are made of highly corrosion resistant stainless steel. Built to withstand years of exposure in snow, ice, and salt air environments, these brackets and the entire lightbar will provide years of reliable service.

Specifications

Product description

Break resistance

Corrosion-free brackets: Yes, included

ECE R10: No

ECE R149: No

Heat sink: 13-piece .06 in

Impact protection rating (IK): IK07

Installation angle: 360°

Material: Aluminum die-cast

Number of LEDs: 10x 5W

Ingress protection rating (IP): IP68 & IP69K

Accessories (optional): additional brackets

ECE reference number: no

Offroad boost: No

One-piece body design

Operating temperature: -40° F to 176° F

Plug type: Connector with 1.4m cable

Scratch resistant lens

Storage temperature: -40° F to 176° F

Technology: LED

Electrical characteristics

Voltage [V]: 9-30 Volt DC

Ordering information

Order entry: UD5011LYX1

GOC: 78004723

Packaging Data

EAN1: 046678004728

EAN3: 50046678004723

Packed product information

Pack Quantity: 1

MOQ (for professionals): 4

Length [in]: 13.78

Width [in]: 3.54

Height [in]: 3.54

Gross weight box: 1.61 lb.

Outerpack information

Length [in]: 14.57

Width [in]: 7.87

Height [in]: 7.87

Gross weight per piece [lb]: 6.61

Light characteristics

Beam length 1 lux: 1050 ft.

Beam length 1 lux (boost): N/A

Beam length 3 lux (boost): N/A

Beam width 1 lux: 196 ft.

Color temperature: 3000 K

Light output (effective lumen): 1800

Light output in Boost mode (ef): N/A

