

Philips Ultinon Drive
5018L
50 Double Row LED
Lightbar

Sturdy one-piece body

IP69K waterproof
Corrosion-free stainless steel
Trouble-free operation

LUMUD5018LX1



Brilliant LED lighting for off-road adventures

Bright, long beam for superior visibility

For drivers who demand the maximum of themselves and their machines, we offer Philips Ultinon Drive 5000 series LED lightbars. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced LED lightbars can light the way.

Easy installation

- Trouble-free operation

Bright long beam for Off-road adventure

- Bright, long beam for superior visibility

Off-road auxiliary lights

- Offering a mid-day color temperature up to 6500K

Powerful brightness, Rugged performance

- Bright, long beam for superior visibility

Durable equipment for challenging conditions

- IP69K waterproof to master the elements

PHILIPS

50 Double Row LED Lightbar

Sturdy one-piece body IP69K waterproof, Corrosion-free stainless steel, Trouble-free operation

Specifications

Product description

- Break resistance
- Corrosion-free brackets: Yes, included
- ECE R10: No
- ECE R149: No
- ECE reference number: No
- Heat sink: 13-piece 1.5mm
- Impact protection rating (IK): IK07
- Ingress protection rating (IP): IP68 & IP69K
- Installation angle: 360°
- Material: Aluminum die-cast
- Number of LED's: 100x 5W
- Offroad boost: No
- One-piece body design
- Operating temperature: -40° F to 176° F
- Plug type: Connector with 1.4m cable
- Scratch resistant lens
- Storage Temperature: -40° F to 176° F
- Technology: LED
- Accessories (optional): Additional brackets

Light characteristics

- Color temperature: 6500 K
- Beam length 1 lux: 2500 ft.
- Beam length 1 lux (boost): N/A
- Beam length 3 lux: 1444 ft.
- Beam length 3 lux (boost): N/A
- Beam width 1 lux: 295 ft.

- Beam width 3 lux: 197 ft.
- Light output (effective lumen): 12000
- Light output in Boost mode: N/A

Electrical characteristics

- Voltage: 9-36 Volt DC

Ordering information

- Order entry: UD5018LX1
- GOC: 78004082

Packaging Data

- EAN1: 046678004087
- EAN3: 50046678004082

Packed product information

- Width: 1.94 in.
- Height: 3.31 in.
- Gross weight box: 8.70 lb.
- Net weight product: 47.46 lb.
- MOQ (for professionals): 2
- Length: 51.97 in.

Outerpack information

- Length [in]: 53.15 in.
- Width [in]: 4.33 in.
- Height [in]: 4.33 in.

LUMUD5018LX1/50

Highlights

Waterproof for durable light

One piece aluminum housing offers best in class IP68 and IP69K waterproof ratings.

Unsurpassed illumination

Match your LED headlights and LED Pods with a modern 6500K LED bar.

Superior visibility

Bright, long beam for superior visibility

Trouble-free

Trouble-free operation

Superior visibility

Up to 2,500 feet of down road, maximizing night time visibility in addition to your led headlight bulbs.



Issue date 2023-10-06

Version: 4.4.1

© 2023 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com