

| Reolink-Video-Doorbell-WiFi-Specifications |                       |                                                                                                                                         |
|--------------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
|                                            | Model                 | Reolink Video Doorbell WiFi                                                                                                             |
| Video & Audio                              | Image Sensor          | 1/2.7" CMOS Sensor                                                                                                                      |
|                                            | Video Resolution      | Default: 2560X1920 (5 megapixels) @20FPS                                                                                                |
|                                            | Lens                  | f=2.26mm F=2.0, with IR cut                                                                                                             |
|                                            | Video Format          | H.264                                                                                                                                   |
|                                            | Field of View         | Horizontal: 134°                                                                                                                        |
|                                            |                       | Vertical: 97°                                                                                                                           |
|                                            |                       | Diagonal: 180°                                                                                                                          |
|                                            | Pre-Motion Recording  | Support                                                                                                                                 |
| Power                                      | Audio                 | Two-way audio, noise reduction, echo suppression                                                                                        |
|                                            | Quick Replies         | Support                                                                                                                                 |
|                                            | Hardwired             | 12-24VAC 50/60Hz, DC 24V                                                                                                                |
| Interfaces                                 | Power                 | Power port                                                                                                                              |
|                                            | System                | Reset button                                                                                                                            |
|                                            | Ethernet              | One 10M/100Mbps RJ45                                                                                                                    |
|                                            | Storage               | Micro SD card slot (Max. 256GB), works with Reolink NVR                                                                                 |
|                                            | Audio                 | Built-in 2 microphones & a speaker                                                                                                      |
| WiFi                                       | Wireless Standard     | IEEE 802.11a/b/g/n                                                                                                                      |
|                                            | Operating Frequency   | 2.4GHz/5GHz                                                                                                                             |
|                                            | Wireless Security     | WPA-PSK/WPA2-PSK                                                                                                                        |
| Software                                   | Frame Rate            | Mainstream: 2fps - 20fps (default: 20fps)                                                                                               |
|                                            |                       | Substream: 4fps - 15fps (default: 10fps)                                                                                                |
|                                            | Code Rate             | Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)                                                                                     |
|                                            |                       | Substream: 64Kbps - 512Kbps (default: 256Kbps)                                                                                          |
|                                            | Browsers Supported    | Edge, Chrome, Firefox, Safari                                                                                                           |
|                                            | OS Supported          | PC: Windows, Mac OS; Smartphone: iOS, Android                                                                                           |
|                                            | Smart Alarm           | Motion detection/person detection; visit notification                                                                                   |
|                                            | Recording Modes       | Motion recording (default); 24/7 recording; scheduled recording                                                                         |
|                                            | Protocols & Standards | HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P                                                              |
| Working Environment                        | Work with             | Google Assistant                                                                                                                        |
|                                            | Temperature           | Operating temperature: -10°C~+50°C (14°F~122°F)                                                                                         |
|                                            | Humidity              | Operating humidity: 10% ~ 90%                                                                                                           |
| Size & Weight                              | Waterproof            | Support                                                                                                                                 |
|                                            | Dimension             | 133mm(H)x48mm(W)x23mm(T)                                                                                                                |
|                                            | Weight                | 96g                                                                                                                                     |
| Warranty                                   | Limited Warranty      | 2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> . |