

HP Universal Photo-realistic Paper 195 g/m²



A highly versatile photo-realistic paper ideal for indoor and outdoor applications that demand superior image quality. Designed to maximize productivity, this high-performance media features a quick dry time and water resistance without lamination.

- HP Universal Photo-realistic Paper delivers quality that rivals prints made with photo-based papers, making it the ideal media for a wide range of graphic display applications.
- HP Universal Photo-realistic Paper is easy to use, which enables greater productivity.

- HP Universal Photo-realistic Paper is a paper-based media for complete solvent printer solution, that delivers vibrant, photo-realistic prints for high-impact displays, anywhere.

Business users such as print service providers, copy shops and sign shops looking for outstanding image quality for high-impact signs and displays.

HP Universal Photo-realistic Paper 195 g/m²

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Whiteness	195 g/m² per 150 536 Test Method		
Weight	8.4 mil/215 microns per ISO 534 Test Method		
Thickness	Greater than 98% per DIN53146 Test Method		
Opacity	Greater than 92% per X-Rite 938 Test Method		
Brightness	Greater than 98 per CIE Ganz 82 Test Method		
Lamination	Cold lamination. Can be laminated with commercially available pressure-sensitive laminating films. Visit HP's website for more information on lamination partners at: www.hp.com/go/designjet/supplies		
Mounting	With glue for billboard application		
Finish	Semi-gloss		
Tear resistant	Greater than 22.4 N per ASTM D1004 Test Method		
Operating temperature	15 to 30° C		
Operating humidity	20 to 70% RH		
Lightfastness (Indoor Home or Office) UV Ink	Greater than 1 year with pigmented Eco Solvent Ink		
Waterfastness	Delta OD less than 0.05		
Dry time	20 minutes (@ 23°C, 50% RH)		
Shelf time	2 years, unopened in original packaging		
Storage temperature	15 to 30° C		
Storage humidity	20 to 70% RH		
Country of origin	Made in Germany		
Ordering information	Product Numbers	Roll sizes	UPC codes
	Q8686AE	914 mm x 45.7 m	8 82780-36565 0
	Q8687AE	1372 mm x 45.7 m	8 82780-36566 7
Warranty	HP Large Format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the user is unsatisfied with HP Large Format printing material they should contact their HP reseller.		

©2006 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit
<http://www.hp.com/go/designjet/supplies>

4AA0-4445 EEE 03/06

