

Philips
Digital audio cable

4 ft
Pro Series

SWW1601U



Experience Advanced Sound

with this digital coaxial audio cable

Experience Hi-definition sound while transferring audio signals between your components. Advanced construction delivers superior sound performance.

Enjoy advanced sound quality

- 24 carat gold-plated connectors optimize signal
- 99.97% Oxygen-Free Copper (OFC)
- Split center pin for optimal signal transfer

Enjoy extended durability

- Protective metal shell for extended durability
- Flexible PVC jacket

Protects against signal loss

- Dielectric insulation
- Triple shielding

Environmentally friendly

- Environmentally friendly lead-free construction

PHILIPS

Specifications

Packaging dimensions

- Packaging dimensions (W x H x D): 18.0 x 26.9 x 5.1 cm
- Packaging dimensions (W x H x D): 7.1 x 10.6 x 2 inch
- Nett weight: 0.115 kg
- Nett weight: 0.254 lb
- Gross weight: 0.275 kg
- Gross weight: 0.606 lb
- Tare weight: 0.160 kg
- Tare weight: 0.353 lb
- UPC: 6 09585 18081 9
- Number of products included: 1
- Packaging type: Carton

Outer Carton

- Outer carton (L x W x H): 30.0 x 23.9 x 22.1 cm
- Outer carton (L x W x H): 11.8 x 9.4 x 8.7 inch
- Nett weight: 0.460 kg

- Nett weight: 1.014 lb
- Gross weight: 1.690 kg
- Gross weight: 3.726 lb
- Tare weight: 1.230 kg
- Tare weight: 2.712 lb
- GTIN: 1 06 09585 18081 6
- Number of consumer packagings: 4

Inner Carton

- Inner carton (L x W x H): 27.9 x 10.9 x 20.1 cm
- Inner carton (L x W x H): 11 x 4.3 x 7.9 inch
- Nett weight: 0.230 kg
- Nett weight: 0.507 lb
- Gross weight: 0.650 kg
- Gross weight: 1.433 lb
- Tare weight: 0.420 kg
- Tare weight: 0.926 lb
- GTIN: 2 06 09585 18081 3
- Number of consumer packagings: 2

Highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

Dielectric insulation

Superior insulation material separates the center conductor from the braided shield. By isolating the conductors, it maintains signal integrity, ensuring the best picture quality and optimum data transfer.

Triple shielding

Provides protection against outside noise and interference that can degrade signal clarity.

Metal shell

The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

split center pin

Split center pin for optimal signal transfer

Lead-free construction

Lead-free construction of environmentally friendly materials.

