

HP Opaque SCRIM



A 15-mil, matte opaque PVC banner paper comprised of tear-resistant polyester fabric embedded between two white vinyl layers. A special ink-receptive coating makes the paper water-resistant and gives it good colour brilliance and edge definition with UV pigment-based inks.

- Provides an easy-to-use material for banners, decorating and indoor and outdoor signs.
- This versatile media is stretchable, punchable and accepts liquid laminates.

- The media offers flexible printing opportunities with dye and UV compatibility.
- The media offers opacity, water-resistance, lightfastness and weather-resistance.
- Offers user a whiter, brighter vinyl banner material with a blockout layer for 100% opacity.

This product can be used by sign shops, print service providers and others who have a need for excellent quality inkjet banners with 100% opacity.

HP Opaque SCrim

Compatibility

HP Designjet printers

HP Designjet 5500 series	HP No. 81 dye/83 UV ink supplies
HP Designjet 5000 series	HP No. 81 dye/83 UV ink supplies
HP Designjet 3000 series	HP Designjet CP ink systems dye/UV
HP Designjet 2000 series	HP Designjet CP ink systems dye/UV
HP Designjet 800 series	HP No. 10, 11 & 82 ink supplies
HP Designjet 500 series	HP No. 10, 11 & 82 ink supplies

HP ink supplies

Non-HP large format printers

Epson 9500 (Pigment)
Epson 9000 (Dye)
Mutoh RJ 6000/Falcon

Weight	496 g/m ²		
Thickness	15.3 mils/389 micrometres		
Whiteness	147 per CIE Ganz 82 test method		
Opacity	> 99%		
Lamination	Liquid lamination		
Mounting	Media can be welded on the back side by thermic and inductive high frequency		
Tear Resistance	1150 MD (N 50mm), 700 CD (N 50mm)		
Operating Temperature	15-35°C		
Operating Humidity	20-80%		
Lightfastness	HP 5000 series UV indoor: estimated > 24 years, HP 5000 series UV commercial window: estimated 16 months, HP 5000 series UV outdoor conditions: estimated 2-3 months (real test), HP 5000 series dye indoor: estimated 10 months, HP CP series UV indoor: estimated > 34 years, HP CP series UV commercial window: estimated 18 months, HP CP series UV outdoor: estimated 2 to 3 months, HP CP series dye indoor: estimated 17 months, HP 800 and 500 series indoor: estimated 8 months		
Waterfastness	Drip test - Yes with UV. Wet rub off - Acceptable after 24 hours.		
Ink compatibility	Dye and UV ink supplies		
Dry Time	HP 5000 series: Dye - ≤ 2.5 minutes, UV - ≤ 3.5 minutes HP CP series: ≤ 1 minute		
Shelf Time	6 months		
Country of Origin	Switzerland		
Ordering Information	Product Numbers	Roll sizes	UPC codes
	Q1898B	914mm x 15m	8 08736-63085 6
	Q1899B	1067mm x 15m	8 08736-63086 3
	Q1901B	1372mm x 15m	8 08736-63087 0
	Q1902B	1524mm x 15m	8 08736-63088 7
Warranty	HP Large Format Printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the user is unsatisfied with HP Large Format Printing material they should contact their HP reseller.		

© 2003 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit www.hp.com/go/designjet/supplies

5982-1437 EEE, 09/2003

