



Impact Drill

PSB 530 RE

PSB 530 RE: High in power,
small in size

[Go to product](#)



Key product features

- As easy as can be: compact design with softgrip, low weight (only 1.6 kg) and outstanding handling ensure optimum user comfort and maximum performance for every job
- Powerful 530 W motor and 10 mm drilling diameter in masonry – making even hard jobs easy
- Bosch Electronic speed control: “accelerate” from 0 – max. using the trigger switch, which enables fingertip control of the power, e.g. when starting to drill in smooth surfaces and when driving screws

Other product advantages

- Keyed chuck for safe and easy bit changes
- Forward/reverse rotation
- Convenient work due to integrated switch for continuous operation
- Dust extraction port – dust extraction available as an optional accessory
- Screwdriving/Drilling/Impact drilling function switch for material-specific work
- New cable guide with hanging hook for practical storage

Comes complete with

- Plastic case
- Friction ring (2 600 206 003)
- Depth stop (2 603 001 009)
- Auxiliary handle (2 609 255 727)

Part number: 0603127072

EAN code: 3165140722261



Impact Drill

PSB 530 RE

Technical data

Power input: 530 W

Power output: 228 W

Max. torque: 7,5 Nm

No-load speed: 50 – 3.000 rpm

Impact rate: 33.000 bpm

Machine weight: 1,6 kg

drilling range

Max. drilling diameter in concrete: 10 mm

Max. drilling diameter in steel: 10 mm

Max. drilling diameter in wood: 20 mm

Screw diameter max.: 5 mm

Noise / vibration information

Measured values determined according to EN 60745.

Total vibration values (vector sum of three directions).

Drilling in metal

Vibration emission value ah: 4.0 m/s²

Uncertainty K: 1.5 m/s²

Impact drilling in concrete

Vibration emission value ah: 33.0 m/s²

Uncertainty K: 3.5 m/s²

Screwdriving

Vibration emission value ah: 2.5 m/s²

Uncertainty K: 1.5 m/s²

Thread-cutting

Vibration emission value ah: 2.5 m/s²

Uncertainty K: 1.5 m/s²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 97 dB(A); Sound power level 108 dB(A). Uncertainty K= 3 dB.



Functions



Power input

530 watts



Bosch Electronic

Speed control using the trigger switch



Compact design

Compact design, low weight

Functions

Keyed chuck

Right-hand/left-hand rotation

Bosch Electronic

Softgrip

Application: screwdriving / drilling / impact drilling