



HP Photosmart 325 printer series (Q3414B) - Specifications



» Overview

Specifications

» Supplies & Accessories

Printing System

Print technology	HP Thermal Inkjet
Colour Printing Technology	Photoret III
Print Head Nozzles	600 colour ink nozzles
Print Quality (Colour, Best Quality)	Up to 4800 x 1200-optimised dpi colour on HP Premium Photo paper when printing from a computer and 1200-input dpi
Print Speed (Colour Photo, Draft Quality) on Photo Paper	Up to 45 sec (when printing from a computer)
Print Speed (Colour Photo, Normal Quality) on Photo Paper	Up to 60 sec
Print Speed Footnote	Dependent upon type, print mode, and approximate figures. Exact speed will vary depending on the system configuration, software program, and document complexity.

Photo Printing and Smart Features

Software Included	HP Image Zone Software for Microsoft® Windows® and Macintosh, with HP Instant Share™ software
Battery Recharge Time	4 hours

Standard Paper Trays	1
Maximum Number of Paper Trays	1
recommended media	Photo paper: 10 x 15 cm, plain paper accepted
Custom Media Sizes	10 x 15 cm
Standard Media Sizes	A6, L
recommended media weight	HP Photo Papers up to 280 g/m2
Maximum Input Capacity	Up to 20 sheets
Standard Output Capacity	Up to 20 sheets
Duplex Print Options	None (not supported)
Standard Memory	32 MB

Other technical information

Compatible Operating Systems	Microsoft® Windows® 98, 2000 Professional, Me, XP Home and XP Professional; Mac OS X v 10.1.5, 10.2, 10.3
Standard Connectivity	1 USB port - compatible with USB 2.0 specifications, 5 memory card slots
Optional Connectivity	Bluetooth printing with optional HP bt300 Bluetooth® wireless adapter
Minimum System Requirements	For all systems: 4x CD-ROM drive, SVGA monitor (800 x 600 with 16-bit colour), USB port and USB cable (not included); for PC systems: Pentium® II (or equivalent) or greater, Microsoft® Windows® 98, 2000 Professional, Me, XP Home and XP Professional, Microsoft Internet Explorer 5.5 or later, 600 MB free hard disk space (2 GB recommended), 64 MB RAM (256 MB recommended); for Mac systems: G3 processor or greater, Mac OS X v 10.1.5, 10.2, 10.3, 500 MB free hard disk space, 128 MB RAM (256 MB recommended)
Minumum System Requirements for Macintosh	4x CD-ROM drive, SVGA monitor (800 x 600 with 16-bit colour), USB port and USB cable (not included), G3 processor or greater, Mac OS X v 10.1.5, 10.2, 10.3, 500 MB free hard disk space, 128 MB RAM (256 MB recommended)
Standard Printer Languages	HP PCL 3 GUI, PML
Acoustic Power Emissions	5.5 B(A)
Dimensions (w x d x h)	220 x 115 x 118 mm
Maximum Dimensions (W x D x H)	300 x 200 x 233 mm
Weight	1.2 kg

Package Weight	2.1 kg
Power consumption	14.4 watts average (printing), 6.2 watts average (non-printing)
power supply type	External power supply module
Power Requirements	Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz)
Operating Humidity Range	5 to 95% RH
Recommended Operating Temperature Range	15 to 35° C
Non-Operating Humidity	5 to 95% RH
Recommended Humidity Operating Range	20 to 80% RH
Electromagnetic Compatibility	IEC 61000-4-2:1995, IEC 61000-4-3:1995, IEC 61000-4-4:1995, IEC 61000-4-5:1995, IEC 61000-4-6:1996, IEC 61000-4-11:1994, IATA 902, EN55022 CISPR 22:1997, EN55022 CISPR 22:1997, FCC Part 15 Class B
Safety	IEC 60950: third edition: 1999; EN 60950:2000; UL 1950/CSA22.2 No. 950, third edition: 1995; NOM 019-SFCI-1993; GB4943:2001
Energy Star Certified	Yes
Warranty	One-year limited hardware warranty backed by HP Customer Care, service and support.