

Product data sheet

Specifications



EasyLogic PM2220, Power & Energy meter, up to the 15th harmonic, LCD display, RS485, class 1

METSEPM2220

Product availability: Stock - Normally stocked in distribution facility

Price*: 633.31 USD

Main

Range	EasyLogic
Product Name	EasyLogic PM2200
Device Short Name	PM2220
Product Or Component Type	Power meter

Complementary

Device Application	Power monitoring Sub billing
Power Quality Analysis	total harmonic distortion up to the 15th harmonic
Type Of Measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
Metering Type	Active, reactive, apparent energy (signed, four quadrant) Current I, I1, I2, I3 Peak demand currents Peak demand power PM, QM, SM Unbalance current Active power P, P1, P2, P3 Reactive power Q, Q1, Q2, Q3 Demand power P, Q, S Voltage U, U21, U32, U13, V, V1, V2, V3 Apparent power S, S1, S2, S3 Calculated neutral current
Accuracy Class	Class 1 active energy IEC 62053-21 Class 1 reactive energy IEC 62053-24 Class 5 harmonic distortion (I THD & U THD)
Measurement Accuracy	Apparent power +/- 1 % Active energy +/- 1 % Reactive energy +/- 1 % Active power +/- 1 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
Measurement Current	5...6000 mA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Measurement Voltage	35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT
Frequency Measurement Range	45...65 Hz
[Us] Rated Supply Voltage	44...277 V AC 45...65 Hz +/- 10 % 44...277 V DC +/- 10 %
Network Frequency	50 Hz 60 Hz
Ride-Through Time	100 ms 120 V AC typical 400 ms 230 V AC typical 50 ms 125 V DC typical
Line Rated Current	1 A 5 A
Maximum Power Consumption In Va	6 VA 277 V AC
Maximum Power Consumption In W	3.3 W power lines (AC)) 2 W 277 V power lines (DC))
Input Impedance	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)
Tamperproof Of Settings	Protected by access code
Display Type	Backlit LCD
Display Colour	Monochrome
Display Resolution	128 x 128 pixels
Demand Intervals	Configurable from 1 to 60 min
Information Displayed	Demand current past value) Demand current present value) Demand power past value) Demand power present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude
Control Type	4 x button
Local Signalling	Red LED output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED module operation and integrated communication
Number Of Inputs	0
Number Of Outputs	0
Communication Port Protocol	Modbus RTU 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires 2500 V
Communication Port Support	Screw terminal block RS485
Data Recording	Time stamping Min/max for 8 parameters
Function Available	Real time clock
Sampling Rate	64 samples/cycle
Cybersecurity	Enable/disable communication ports
Communication Service	Remote monitoring

Language	Spanish French English Russian Portuguese German Chinese
Product Certifications	CE IEC 61010-1 CULus UL 61010-1 CULus CSA C22.2 No 61010-1 RCM EAC C-tick
Mounting Mode	Clip-on
Mounting Position	Vertical
Mounting Support	Framework
Provided Equipment	1 x Installation guide
Measurement Category	Category III 480 V Category II 480...600 V
Electrical Insulation Class	Double insulation Class II
Flame Retardance	V-0 conforming to UL 94
Connections - Terminals	Current transformer screw connection bottom) 6 Voltage inputs screw connection top) 4
Material	Polycarbonate
Width	3.78 in (96 mm)
Depth	Total 3.00 in (76.09 mm) Embedded 2.43 in (61.64 mm)
Height	3.78 in (96 mm)
Net Weight	10.58 oz (300 g)
Compatibility Code	PM2220

Environment

Service Life	7 year(s)
Ip Degree Of Protection	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
Relative Humidity	5...95 % 122 °F (50 °C)
Pollution Degree	2
Ambient Air Temperature For Operation	14...140 °F (-10...60 °C)
Ambient Air Temperature For Storage	-13...158 °F (-25...70 °C)
Operating Altitude	<= 6561.68 ft (2000 m)
Electromagnetic Compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC Part 15 class A

Overvoltage Category	III
----------------------	-----

Ordering and shipping details

Category	US10PL109734
Discount Schedule	0PL1
Gtin	3606480800177
Returnability	Yes
Country Of Origin	IN

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.50 in (8.9 cm)
Package 1 Width	4.80 in (12.2 cm)
Package 1 Length	4.61 in (11.7 cm)
Package 1 Weight	9.52 oz (270 g)

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free	
 RoHS Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information