

Product data sheet

Specifications



SmartX Temperature Sensor, Resistive 10K Type 3 Thermistor, Blank, with Matte White Cover

SLASXXX

Main

Product or component type	Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	24 mm
Height	115 mm
Width	85 mm
Standards	UL 916 FCC part 15 class B
Colour	White
Ambient air temperature for operation	0...50 °C
Relative humidity	0...95 %
Sensor type	10 kOhm T3 thermistor
Product name	SmartX Living Space Sensor
Surface finish	Matt
Range	SpaceLogic

Complementary

Device presentation	Complete product
Connections - terminals	Screw - 2 cable(s) (AWG 24...AWG 18)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers
Material	ABS (acrylonitrile butadiene-styrene)
Display type	Without display
Communication port protocol	-- 2 wires

Environment

Measurement range	0...50 °C temperature
-------------------	-----------------------

Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
------------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	9.7 cm
Package 1 Length	14.2 cm
Package 1 Weight	138 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.76 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)