



Product data sheet

Power tools for trade & industry

Cordless Rotary Hammer BITURBO with SDS max

GBH 18V-45 C Professional



from GBP 808.27*

* Price including VAT

Cordless freedom with corded performance – the heavy duty all-rounder for concrete drilling and chiselling

Part number: 0 611 913 000

[> More product information](#)

Technical Data

webshop-pdp-section-technical-data-table-key-
Technical data

Max. impact energy	12.5 J
Impact rate at rated speed	0 – 2,760 bpm
Rated speed	0 – 305 rpm
Tool holder	SDS max

webshop-pdp-section-technical-data-table-key-
Size and weight

Weight excl. battery	8 kg
----------------------	------

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	8,5 m/s ²
Uncertainty K	1,5 m/s ²

Chiselling

Vibration emission value ah	7,0 m/s ²
Uncertainty K	1,5 m/s ²

Noise

Sound pressure level	94 dB(A)
Sound power level	105 dB(A)
Uncertainty K	3 dB

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages

- Cordless freedom with corded performance thanks to BITURBO Brushless technology.
- Lighter than comparable corded products thanks to a highly optimized drive train, even with attached ProCORE18V 12.0Ah battery
- KickBack Control for reduced hazard of sudden tool reactions and Soft Start EPC & ASC for a comfortable and precise work process.

