

PHILIPS

40 inch LED light bar

Ultinon Drive 5000

Off-road auxiliary lights

9800 lm, 724 m beam length

IP69K waterproof

Sturdy corrosion-free body

LUMUD5017LX1



Brilliant LED lighting for off-road adventures

Bright, durable gear for overland journeys

For drivers who demand the maximum of themselves and their machines, we offer the Philips Ultinon Drive 5000 series LED lightbars. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced LED lightbars can light the way.

Greater safety with powerful brightness

- Long, bright beam for superior visibility

Durable equipment for challenging conditions

- Sturdy one-piece body for tough environments
- IP69K waterproof to master the elements
- Corrosion-free body, stainless-steel mounting brackets

Easy and flexible installation

- Accessories for simpler fitment

Ultinon Drive 5000

40 inch LED light bar

LUMUD5017LX1/10

Specifications

Product description

Cable length: 1.4 m
Boost mode activation: No
Break resistance
ECE R10: No
ECE R149: No
Impact protection rating (IK): IK07
Ingress protection rating (IP): IP68 and IP69K
Installation angle: 360°
Material: Aluminium die-cast
Number of LEDs: 80x 5W
Off-road boost: No
One-piece body design
Operating temperature: -40° C to 80°C
Scratch-resistant lens
Storage Temperature: -40° C to 80° C
Technology: LED
Width: 30 inch
Boost function installation: No
Compatible with: N/A
Accessories (optional): LUMUD1007WX1
corrosion-free brackets: yes, included
Parking position light: No

Plug type: 2-pin DT Connector with 1.4m cable
Heat sink: 13-piece 1.5 mm
Fuse: No
Relay: No
Switch On/Off: No
Number of connector plugs: 1

Light characteristics

Colour temperature: 6500 K K
Beam length 3 lux-m: 418 m
Beam length 1 lux-m: 724 m
Beam width 3 lux-m: 60 m
Beam width 1 lux-m: 90 m
Effective lumen output: 9800 lumen
Raw lumen output: 38080 lumen
Effective lumen output (boost): N/A

Electrical characteristics

Wattage: 145 W
Voltage: 9-36 Volt DC V

Ordering information

Order entry: UD5017LX1
GOC: 02432933

Packaging Data

EAN1: 8719018024329
EAN3: 8719018024336

Packed product information

Pack Quantity / MOQ: 1
MOQ (for professionals): 2
Box dimensions-L (mm): 1100
Box dimensions-W (mm): 110
Box dimensions-H (mm): 110
Net weight product-g: 2690
Gross weight box-g: 3140

Outer pack information

Length: 115 cm
Width: 25 cm
Height: 14 cm
Gross weight per carton: 7600 g

