

EM-KS2AEU-B

Electric scooter

Electric scooter with built-in display, dual rear suspension and app control.



HIGHLIGHTS

Wheel size: 10" Pneumatic tyre

Max load: 120 kg

Range per charge: 40 km

Certified battery 36V 10.4Ah

IPX4 certification

Mechanical bell

Control App

Dual brake systems

Easy to handle

Hidden cables

Rear Suspension

USB Charging Port

Charging Time: 6-8 hours

A comfortable and environmentally friendly way to transport yourself with the Sharp electric scooter. The easy folding system allows you to take it with you, simply and uncomplicated.

e-scooter Features

Display	LED
APP Control	Yes
Battery (Ah)	10.4
Battery (Voltage)	36
Battery (Wattage)	374
Battery Charging Time (hours)	6-8
Bell	Yes
Tyre Pressure (PSI)	36
Tyres	Pneumatic
USB Port	Yes
Wheel Size (inches)	10
Braking	Disc brake / Power off brake
Charger Input (VAC/A)	100-240/1.8
Charger Output (VDC/A)	42/1.5
Driving Mechanism	Rear Wheel Brushless Motor (350W)
Foldable	Yes
IP Rating	IPX4
Maximum Incline (degrees)	15
Maximum Load (kg)	120
Maximum Speed (km/h)	25
Motor Power (Watts)	350
Range per Full Charge (km)	40
Start Mode	Kick Start
Suspension	Rear
Brake - Electronic	Yes
Brake - Rear Wheel	Disc
Display Type	Standard
Type of Headlight	Standard

Power Information

Power Requirements	100-240VAC 50/60HZ 1.8A
Power Consumption	6.4
Standby Power Consumption	0
Off Mode Power Consumption (W)	0
Safety Logo Certification	PLEV, RED, LVD, EMC, REACh, RoHS
Plug	CE/UK Plug +adaptor
Auto Power Off	Yes
External AC Adapter	Yes

Logistic Information

Box Size (W x H x D in mm)	205 x 520 x 1215
Gross Weight (kg)	21.6
Units on EU Pallet 1.8m	9
Container Load 40HQ	510
Container Load 40	445
Container Load 20	208
Dimensions Folded (W x H x L in mm)	470 x 498 x 1180
Dimensions Unfolded (W x H x L in mm)	470 x 1200 x 1180
Foot Plate Size (W x L in mm)	160 x 483
Foot Plate to Top of Handlebars (mm)	1025
Ground to Foot Plate (mm)	180
EAN	5903802466775