

## KVR667D2S5/512

### 512MB 64M x 64-Bit DDR2-667

### CL5 200-Pin SODIMM


#### DESCRIPTION:

This document describes ValueRAM's 64M x 64-bit (512MB) CL5 DDR2-667 SDRAM (Synchronous **DRAM**) memory module. The components on this module include eight 64M x 8-bit (16M x 8-bit x 4 Bank) DDR2-667 SDRAM in FBGA packages. This 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

#### FEATURES:

|                                                 |                               |
|-------------------------------------------------|-------------------------------|
| ✓ Clock Cycle Time (tCK) CL=5                   | 3ns (min.) / 8ns (max.)       |
| ✓ Row Cycle Time (tRC)                          | 54ns (min.)                   |
| ✓ Refresh to Active/Refresh Command Time (tRFC) | 105ns                         |
| ✓ Row Active Time (tRAS)                        | 39ns (min.) / 70,000ns (max.) |
| ✓ Single Power Supply of                        | +1.8V (+/- .1V)               |
| ✓ Power                                         | 1.595 W (operating)           |
| ✓ UL Rating                                     | 94 V - 0                      |

**Note:** The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 30mm.



**Figure 1: KVR667D2S5/512 200-Pin SODIMM**