

Product data sheet

Specifications



servo motor BMH - 62.5 Nm - 3800 rpm - untapped shaft - with brake - IP65/IP67

BMH2052P27F2A

Main

Product or component type	Servo motor
Device short name	BMH
Maximum mechanical speed	3800 rpm
Continuous stall torque	62.5 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 62.5 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Peak stall torque	170 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 170 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal output power	6500 W for LXM32.D72N4 at 24 A, 400 V, three phase 6500 W for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal torque	41.6 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 41.6 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal speed	1500 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 1500 rpm for LXM32.D72N4 at 24 A, 480 V, three phase
Product compatibility	LXM32.D72N4 at 400...480 V three phase
Shaft end	Smooth shaft
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	32768 points/turn x 4096 turns
Holding brake	With
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Range compatibility	Lexium 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	24.2 A
Continuous power	7.85 W
Maximum current Irms	72 A for LXM32.D72N4
Maximum permanent current	96.8 A
Second shaft	Without second shaft end
Shaft diameter	38 mm

Shaft length	80 mm
Feedback type	Multiturn SinCos Hiperface
Holding torque	80 N.m holding brake
Motor flange size	205 mm
Number of motor stacks	2
Torque constant	2.6 N.m/A at 120 °C
Back emf constant	161 V/krpm at 120 °C
Number of motor poles	10
Rotor inertia	145 kg.cm²
Stator resistance	0.3 Ohm at 20 °C
Stator inductance	5.6 mH at 20 °C
Stator electrical time constant	18.7 ms at 20 °C
Maximum radial force Fr	4200 N at 1000 rpm 3330 N at 2000 rpm 2910 N at 3000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
Type of cooling	Natural convection
Length	454.5 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Net weight	48.9 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	58.0 kg
Package 1 Height	36 cm
Package 1 width	31 cm
Package 1 Length	73 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months