

# Product data sheet

Specifications



## ION8650 meter 32MB, 9S/29S/36S, 277VAC 60Hz, Ethernet 1I+5O, RMICAN

M8650C0C0E6E1C3A

### Main

|                           |                                 |
|---------------------------|---------------------------------|
| Range                     | PowerLogic                      |
| Device short name         | ION8650C                        |
| Product or component type | Revenue and power quality meter |

### Complementary

|                                 |                                                                                                                                                                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power quality analysis          | up to the 31st harmonic<br>harmonic distortion<br>voltage sag and swell detection<br>programmability (logic and math functions)                                                                                                         |
| Device application              | Energy pulsing and totalisation<br>Co-generation and IPP monitoring<br>Tariff metering<br>Load curtailment<br>Equipment monitoring and control<br>Demand and power factor control<br>Instrument transformer correction                  |
| Type of measurement             | Current<br>Voltage<br>Frequency<br>Apparent power total<br>Power factor total<br>Apparent power per phase<br>Power factor per phase<br>Active power total<br>Active power per phase<br>Reactive power total<br>Reactive power per phase |
| Supply voltage                  | 120...277 V AC 47...63 Hz                                                                                                                                                                                                               |
| Network frequency               | 60 Hz                                                                                                                                                                                                                                   |
| [In] rated current              | 2 A<br>1 A<br>5 A                                                                                                                                                                                                                       |
| Type of network                 | 3P + N<br>3P<br>1P + N                                                                                                                                                                                                                  |
| Power consumption in VA         | 24 VA                                                                                                                                                                                                                                   |
| Maximum power consumption in VA | 33 VA                                                                                                                                                                                                                                   |
| Display type                    | FSTN transfective LCD                                                                                                                                                                                                                   |
| Form designation                | 9S 3-element 4<br>36S 2½-element 4<br>29S 2½-element 4                                                                                                                                                                                  |
| Sampling rate                   | 1024 samples/cycle                                                                                                                                                                                                                      |

|                               |                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement current           | 0.001...24 A                                                                                                                                                                                                                                                                                                                                                  |
| Input type                    | Current 0.01...20 A (impedance 0.05 Ohm)                                                                                                                                                                                                                                                                                                                      |
| Measurement voltage           | 57...277 V AC phase to neutral<br>100...480 V AC phase to phase                                                                                                                                                                                                                                                                                               |
| Number of inputs              | 1 digital 0.001...100 mA 30 V DC                                                                                                                                                                                                                                                                                                                              |
| Measurement accuracy          | Current 0.1 %<br>Voltage 0.1 %<br>Power 0.1 %<br>Power factor 0.1 %<br>Frequency 0.001 Hz<br>Energy 0.1 %                                                                                                                                                                                                                                                     |
| Accuracy class                | Class 0.2S energy conforming to IEC 62053-23<br>Class 0.2 energy conforming to ANSI C12.20<br>Class 0.2S energy conforming to IEC 62053-22                                                                                                                                                                                                                    |
| Number of outputs             | 2 pulse<br>4 form C relay output<br>1 form A triac output                                                                                                                                                                                                                                                                                                     |
| Communication port protocol   | DNP3 at 300...115200 bauds<br>ION at 300...115200 bauds<br>Ansi C12.18 at <= 19200 bauds<br>IEC 61850 ed. 2 at 10/100 Mbit/s<br>TCP/IP at 10/100 Mbit/s<br>DLMS at 300...115200 bauds<br>Modbus at 57600 bauds<br>DNP3 at 10/100 Mbit/s<br>ION at 10/100 Mbit/s<br>Modbus RTU, slave at 300...115200 bauds<br>Modbus TCP, slave at 10/100 Mbit/s<br>EtherGate |
| Communication port support    | RJ45: ETHERNET<br>SUB-D 9: RS485/RS232<br>Terminal block: RS485<br>Infrared                                                                                                                                                                                                                                                                                   |
| Time synchronisation protocol | IRIG-B<br>GPS: Truetime/Datum                                                                                                                                                                                                                                                                                                                                 |
| Data recording                | Time stamping<br>Alarms<br>Sag and swell logs<br>Data logs<br>Revenue logs<br>Event logs<br>GPS synchronisation<br>Harmonics logs<br>Historical logs                                                                                                                                                                                                          |
| Transmission rate             | 10/100 Mbit/s<br><= 19200 bauds<br>300...115200 bauds<br>57600 bauds                                                                                                                                                                                                                                                                                          |
| Memory capacity               | 32 MB                                                                                                                                                                                                                                                                                                                                                         |
| Web services                  | Web server<br>Alarm notification by e-mail<br>Robust security logs<br>Port addressing user designed                                                                                                                                                                                                                                                           |
| Ethernet service              | Enable/disable Ethernet protocols<br>SNMP-Traps and SYSLOG<br>Enable/disable serial ports                                                                                                                                                                                                                                                                     |
| Tamperproof of settings       | RMICAN protected                                                                                                                                                                                                                                                                                                                                              |
| Compatibility code            | ION8650C                                                                                                                                                                                                                                                                                                                                                      |

## Environment

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electromagnetic compatibility | Electrostatic discharge immunity test conforming to IEC 61000-4-2<br>Conducted RF disturbances conforming to IEC 61000-4-6<br>Immunity to impulse waves conforming to IEC 61000-4-12<br>Electrical fast transient/burst immunity test conforming to IEC 61000-4-4<br>Susceptibility to electromagnetic fields conforming to IEC 61000-4-3<br>1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5<br>Conducted and radiated emissions B conforming to CISPR 22 |
| Mounting mode                 | Socket-mounted                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Mounting support              | Enclosure door                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                                       |                                |
|---------------------------------------|--------------------------------|
| Type of installation                  | Indoor installation            |
| Overvoltage category                  | III                            |
| IP degree of protection               | IP65 front face:<br>IP51 back: |
| Relative humidity                     | 5...95 %                       |
| Pollution degree                      | 2                              |
| Ambient air temperature for operation | -40...85 °C                    |
| Ambient air temperature for storage   | -40...85 °C                    |
| Operating altitude                    | 0...3000 m                     |
| Standards                             | ANSI C12.1<br>IEC 62052-11     |
| Width                                 | 178 mm                         |
| Depth                                 | 237 mm                         |
| Height                                | 178 mm                         |
| Product weight                        | 7 kg                           |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 26.0 cm |
| Package 1 Width              | 28.0 cm |
| Package 1 Length             | 44.0 cm |
| Package 1 Weight             | 4.5 kg  |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| California proposition 65  | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>                  |

### Recommended replacement(s)