PHILIPS

Philips Lighting Contact Center
Postbus 22613
1100 DP Amsterdam
I.B.A.S. / C.C.R.I. Numeric 1040
Telefax: 0 20 - 6 94 - 8 71
E-mail: info@philips.com
Last update: 15/04/14

20 Protection class II: the product or component is provided with double or reinforced insulation.
21 Protection class III: the product or component is only suitable for safety extra low voltage supply
22 IP20: Protection against
23 IP44: Protection against splashes
24 The earthing wire always has to be longer than the brown live (L) and blue neutral (N) wire.
25 The product is only suitable for fixed installation (e.g. in a fixed lamp).
26 The product is only suitable for wiring directly to the electrical mains supply.
27 Protection against short circuit: the wires of the cable are in the same or in the same type.
28 Protection against overload: the wires of the cable are in the same or in the same type. Contact your distributor or by an expert, to avoid risks.
29 Connection: The earthing wire flexible cable or cord of this luminaire cannot be replaced. If the cord is damaged, the luminaire shall be destroyed.
30 Lifetime: The lifetime of the LED module in this product and keep within the maximum specified wattage.
31 Protection against dust: IP5X: Dust protected.
32 The product is only suitable for CFL- or LED bulbs (e.g. E14, E27, GU10, G53, ...).
33 The product is not suitable for CFL- or LED bulbs (e.g. E14, E27, GU10, G53, ...).
34 Only a bulb with a diameter of 60 mm can be used. A bulb with a 45 mm diameter must not be used in this luminaire.
35 Only use a globe bulb that has the size of the indicated diameter. Never use a standard incandescent bulb.
36 The product is only suitable for a bulb with bulb safety or a low pressure bulb. An extra safety glass is required.
37 The product is only suitable for a bulb with bulb safety or a low pressure bulb. An extra safety glass is required. Contact your dealer.
38 Glass shade: Use only a bulb with a maximum wattage of 25 watt.
39 The product is equipped with a fuse. If the product is out of order after bulb replacement, the internal fuse has to be replaced. This must be done by a qualified electrician or by an expert. Contact your dealer.
40 Dimmable: dimmable with the supplied dimmer or with a (not included) dimmer connected to the electrical mains. Consult the dimmer manufacturer for more details/ref "www.philips.com/". Consult a qualified electrician or your retail outlet, if in doubt.
41 The product is working with a safety transformer. Use only a safety transformer only with a transformer with identical technical specifications. Consult a qualified electrician or your retail outlet.
42 Use only in dry rooms.
43 Product with time and light setting options. Minimum and maximum is indicated on the icon.
44 Product with time and light setting options. Only for indoor use.
45 Fit reliable screws, have to resist a pull force of 30 N, suitable height as indicated on the icon. The maximum and minimum reach of the detector is also indicated.
46 The standard active angle of detection is 180 degrees and the standard active range is 12 meters. The sensor is 10 meters. The product should be mounted horizontally. For longer life, the bulb should not be at an angle greater than 45 degrees.
47 Ensure not to drill through electrical wiring or any other obstacles when drilling holes for the wall installation!
48 The product is dimmable with the supplied dimmer or with a (not included) dimmer connected to the electrical mains. Consult the dimmer manufacturer for more details/ref "www.philips.com/". Consult a qualified electrician or your retail outlet, if in doubt.
49 The product is working with a safety transformer. Use only a safety transformer only with a transformer with identical technical specifications. Consult a qualified electrician or your retail outlet.
50 Product with time and light setting options. Minimum and maximum is indicated on the icon.
51 Product with time and light setting options. Only for indoor use.
52 Fit reliable screws, have to resist a pull force of 30 N, suitable height as indicated on the icon. The maximum and minimum reach of the detector is also indicated.
53 The standard active angle of detection is 180 degrees and the standard active range is 12 meters. The sensor is 10 meters. The product should be mounted horizontally. For longer life, the bulb should not be at an angle greater than 45 degrees.
54 Ensure not to drill through electrical wiring or any other obstacles when drilling holes for the wall installation!

INSTRUCTIONS DE SÉCURITÉ IMPORTANTES

Ce manuel ß contient les définitions de tous les paramètres et de toutes les caractéristiques techniques pouvoirdonner satisfaction sans risque. Veuillez lire attentivement ce manuel avant installation et suivre les normes de sécurité. Conservez ces parameètres et caractéristiques ne s'appliquent pouvoir plus tard.
Ce produit ne peut être installé et utilisé que par un électricien qualifié. Veuillez consulter le pouvoir avant installation.
- Afin de garantir une installation et une utilisation sûres et adéquates, ainsi qu'un bon fonctionnement du produit, suivez toujours les instructions de sécurité et d'installation ci-dessous.
- Veuillez toujours l'appareil hors tension avant toute opération d'installation, d'entretien ou de réparation.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- En cas de doute, consultez un électricien qualifié ou suivez licences ou contactez votre revendeur. Assurez-vous toujours que le câble de terre (jaune/vert) dépasse les autres conducteurs (marron, bleu ou gris).
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.

Ce manuel ß contient les définitions de tous les parameètres et de toutes les caractéristiques techniques pouvoirdonner satisfaction sans risque. Veuillez lire attentivement ce manuel avant installation et suivre les normes de sécurité. Conservez ces parameètres et caractéristiques ne s'appliquent pouvoir plus tard.
Ce produit ne peut être installé et utilisé que par un électricien qualifié. Veuillez consulter le pouvoir avant installation.
- Afin de garantir une installation et une utilisation sûres et adéquates, ainsi que bon fonctionnement du produit, suivez toujours les instructions de sécurité et d'installation ci-dessous.
- Veillez toujours l'appareil hors tension avant toute opération d'installation, d'entretien ou de réparation.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- En cas de doute, consultez un électricien qualifié ou suivez licences ou contactez votre revendeur. Assurez-vous toujours que le câble de terre (jaune/vert) dépasse les autres conducteurs (marron, bleu ou gris).
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.

TN SAFETY INSTRUCTIONS

Manual ß contains definitions of all potentially applicable parameters & specifications with icons, or per International norms and safety standards. However not all of them may be applicable for this product. Please read carefully & keep for future reference.
This product can only be installed and used by an electrician. Please consult the supplier before installation.
- To ensure correct and safe installation, usage and functioning of the product, always follow these instructions carefully and keep them for future reference.
- Always switch off the power prior to installation, maintenance or repair activities.
- Do not open the product housing. This product does not contain any parts that require mounting of the product. Take into account the weight of the product and the type of wall or ceiling material of the surface.
- In doubt, consult a qualified or licensed electrician or contact your retail outlet. Ensure the product is always installed according to relevant regulations. Certain regulations indicate that electrical products must be installed by an expert. Always ensure that the earthing wire (e.g. Part P for the UK, AS/NZS3000 for AUSTRALIA/NEW ZEALAND) is longer than the brown live (L) and blue neutral (N) wire.
- Always tighten the terminal screws firmly, especially attachments for low voltage wiring (12V) (if applicable). It is highly recommended to regularly check and re-tighten the terminal screws if need be. Observe the correct colour of the wiring before installation: blue (N), brown (L) and if protection (earth), green/yellow or green (E).
- Maintain interior lighting with a dry cloth duster, do not use abrasives or solvents. Avoid liquids on all electrical parts.
- Keep out of sight and out of children's reach.
- If the product is mounted on a metallic surface, this surface must be bonded to the protective earth (PE) of the electrical installation, using a suitable bonding clamp.
- Always consult a professional/qualified electrician if you are in doubt about the product. Verify whether the product and icons shown in part A of these safety instructions.
- Immediately replace a cracked or broken diffuser/cover/shade/globe/glass/lens/lampshade/etc. Use only a manufacturer approved parts.
- It is advised to only use "Philips branded" replacement parts.
- Do not touch the lamp/bulb/LED module/etc. Use a cloth or tissue (e.g. plastic bags...).
- ♻Disposal of the product: Your product is designed and manufactured with high quality materials and components, which can be recycled and reused. When this crossed-out wheeled bin symbol is attached to a product it means the product is covered by the European Directive 2012/19/EU. Please inform yourself about the local waste disposal, separation and collection system for electrical and electronic products. Please act according to your local rules and do not dispose your old products with your normal household waste. The correct disposal of your old product will help prevent potential negative consequences for the environment and human health.

ATTENTION: Below you will find all the explanations with numeric reference to the icons respectively in front of these safety instructions:
1 This product is not suitable for wet locations.
2 This product is not suitable for radiation or radiations, certainly not in the specified zones.
3 The product is suitable for mounting on normally flammable surfaces.
4 The product is not suitable for direct mounting on normally flammable surfaces.
5 The product is not suitable for covering with thermally insulating material.
6 The product is not suitable for use in a hot room.
7 The product is not suitable for use in a hot room.
8 The product is suitable for mounting on the wall or on the ceiling.
9 The product is suitable for mounting on the ceiling only when installed on the icon, between the lamp and the lighted object.
10 IP20: The product is protected against foreign bodies.
11 IP23: The product may be exposed to raindrops falling drops under a maximum angle of 60° to the vertical axis).
12 IP44: The product is splash-proof: it may be exposed to splashing water coming from any direction.
13 IP54: The product is protected against water jets.
14 IP67: The product can be installed into the ground.
15 IP68: The product is protected against immersion up to the indicated depth.
16 IP68: The product is dust tight.
17 IP6X: The product is dust tight.
18 Protection class I: the product or component has an earthing connection. The earth wire (yellow/green) has to be connected to the earth wire of the electrical mains.
19 Protection class II: the product or component has an earthing connection. The earth wire (yellow/green) has to be connected to the earth wire of the electrical mains.
20 Protection class III: the product or component is only suitable for safety extra low voltage supply
21 Protection class III: the product or component is only suitable for safety extra low voltage supply
22 IP20: Protection against
23 IP44: Protection against splashes
24 The earthing wire always has to be longer than the brown live (L) and blue neutral (N) wire.
25 The product is only suitable for fixed installation (e.g. in a fixed lamp).
26 The product is only suitable for wiring directly to the electrical mains supply.
27 Protection against short circuit: the wires of the cable are in the same or in the same type.
28 Protection against overload: the wires of the cable are in the same or in the same type. Contact your distributor or by an expert, to avoid risks.
29 Connection: The earthing wire flexible cable or cord of this luminaire cannot be replaced. If the cord is damaged, the luminaire shall be destroyed.
30 Lifetime: The lifetime of the LED module in this product and keep within the maximum specified wattage.
31 Protection against dust: IP5X: Dust protected.
32 The product is only suitable for CFL- or LED-bulbs (e.g. E14, E27, GU10, G53, ...).
33 The product is not suitable for CFL- or LED-bulbs (e.g. E14, E27, GU10, G53, ...).
34 Only a bulb with a diameter of 60 mm can be used. A bulb with a 45 mm diameter must not be used in this luminaire.
35 Only use a globe bulb that has the size of the indicated diameter. Never use a standard incandescent bulb.
36 The product is only suitable for a bulb with bulb safety or a low pressure bulb. An extra safety glass is required.
37 The product is only suitable for a bulb with bulb safety or a low pressure bulb. An extra safety glass is required. Contact your dealer.
38 Glass shade: Use only a bulb with a maximum wattage of 25 watt.
39 The product is equipped with a fuse. If the product is out of order after bulb replacement, the internal fuse has to be replaced. This must be done by a qualified electrician or by an expert. Contact your dealer.
40 Dimmable: dimmable with the supplied dimmer or with a (not included) dimmer connected to the electrical mains. Consult the dimmer manufacturer for more details/ref "www.philips.com/". Consult a qualified electrician or your retail outlet, if in doubt.
41 The product is working with a safety transformer. Use only a safety transformer only with a transformer with identical technical specifications. Consult a qualified electrician or your retail outlet.
42 Use only in dry rooms.
43 Product with time and light setting options. Minimum and maximum is indicated on the icon.
44 Product with time and light setting options. Only for indoor use.
45 Fit reliable screws, have to resist a pull force of 30 N, suitable height as indicated on the icon. The maximum and minimum reach of the detector is also indicated.
46 The standard active angle of detection is 180 degrees and the standard active range is 12 meters. The sensor is 10 meters. The product should be mounted horizontally. For longer life, the bulb should not be at an angle greater than 45 degrees.
47 Ensure not to drill through electrical wiring or any other obstacles when drilling holes for the wall installation!
48 The product is dimmable with the supplied dimmer or with a (not included) dimmer connected to the electrical mains. Consult the dimmer manufacturer for more details/ref "www.philips.com/". Consult a qualified electrician or your retail outlet, if in doubt.
49 The product is working with a safety transformer. Use only a safety transformer only with a transformer with identical technical specifications. Consult a qualified electrician or your retail outlet.
50 Product with time and light setting options. Minimum and maximum is indicated on the icon.
51 Product with time and light setting options. Only for indoor use.
52 Fit reliable screws, have to resist a pull force of 30 N, suitable height as indicated on the icon. The maximum and minimum reach of the detector is also indicated.
53 The standard active angle of detection is 180 degrees and the standard active range is 12 meters. The sensor is 10 meters. The product should be mounted horizontally. For longer life, the bulb should not be at an angle greater than 45 degrees.
54 Ensure not to drill through electrical wiring or any other obstacles when drilling holes for the wall installation!

INSTRUCTIONS DE SÉCURITÉ IMPORTANTES

Ce manuel ß contient les définitions de tous les parameètres et de toutes les caractéristiques techniques pouvoirdonner satisfaction sans risque. Veuillez lire attentivement ce manuel avant installation et suivre les normes de sécurité. Conservez ces parameètres et caractéristiques ne s'appliquent pouvoir plus tard.
Ce produit ne peut être installé et utilisé que par un électricien qualifié. Veuillez consulter le pouvoir avant installation.
- Afin de garantir une installation et une utilisation sûres et adéquates, ainsi que bon fonctionnement du produit, suivez toujours les instructions de sécurité et d'installation ci-dessous.
- Veillez toujours l'appareil hors tension avant toute opération d'installation, d'entretien ou de réparation.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- En cas de doute, consultez un électricien qualifié ou suivez licences ou contactez votre revendeur. Assurez-vous toujours que le câble de terre (jaune/vert) dépasse les autres conducteurs (marron, bleu ou gris).
- Ne pas dépasser la puissance maximale indiquée sur le produit. Ne pas dépasser la puissance maximale indiquée sur le produit.
- Veillez à toujours bien serrer les vis de borne, en particulier pour les accessoires des installations à basse tension. Les bornes non serrées peuvent provoquer des incendies. Contrôlez régulièrement les bornes et serrez-les si nécessaire.
- Ne pas utiliser ce produit à l'extérieur ou dans des zones humides ou poudreuses.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.
- Ne pas ouvrir le boîtier du produit. Ce produit ne contient aucune pièce réparable par l'utilisateur.

39- Výrobek do nárazových podmínek.
40- Výrobek s hodnotami nastavení Času a světla. Minimum a maximum je uvedeno na ikoně.
41- Výrobek s ochranou proti vniknutí vody IPX4.
42- Výrobek s ochranou proti vniknutí vody IPX5 - výrobek je odolný vůči vodě vyvolané ve formě tlaku vodního paprsku v minimální době stanovené.
43- Standardní výrobek pro pracovní prostředí, nevhodný pro trvalé ponoření.
44- Tento výrobek musí být namontován vodorovně. Chraňte z západní části Dvořnové, neměl by být zdvižné.
45- Výrobek s ochranou proti vniknutí vody.
46- Upozorňujeme na to, že výrobek nevnese ani nevyvolá vodní tlak, jako je tlak vodní.
47- Pokud se výrobek montuje do stropní nebo nadhlavní schránky, je nutné krátký nepřerušený vlákno vyvinout.
48- Elektrické vedení nesmí nikdy být skleněno nebo obrouceno nebo výrobkem a montážním povrchem!
49- Výrobek je vhodný pro vnitřní prostory.
50- Výrobek není vhodný pro venkovní prostory.
51- Namontuje výrobek mimo dosah nakou (IK1 pro dětí, IK2 dospělí).
52- Výrobek je vhodný pro venkovní prostory.
53- Výrobek je také vhodný ostatní výrobky z kolekcí je nevrtání, vyrobení a bezbolo v soubory a montážní krabice. Montážní krabice nejsou součástí balení. Výrobek je vhodný pro ALUMINIUM, ALUMINIUM, ALUMINIUM,