

Philips
Composite A/V cable

5 m

SWV5530



Create a superior viewing experience

with this scart cable

Take your components to superior performance. This high-end cable offers an improved connection for transferring audio/video signals between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimise signal

Enjoy better audio quality

- 4-Cut connectors for secure connections
- Stranded conductor extends durability

Protects against signal loss

- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided reinforced aluminium shielding
- Foam Polyethylene (FPE) Dielectric

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

PHILIPS
sense and simplicity

Composite A/V cable
5 m

Specifications

Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93455 8
- Gross weight: 0.74 kg
- Tare weight: 0.13 kg
- Net weight: 0.61 kg
- Length: 265 mm
- Width: 195 mm
- Height: 100 mm

Inner Box

- EAN/UPC/GTIN: 87 10895 97054 9
- Quantity: 2
- Gross weight: 1.82 kg
- Tare weight: 0.6 kg

- Net weight: 1.22 kg
- Length: 280 mm
- Width: 175 mm
- Height: 210 mm

Outer Box

- EAN/UPC/GTIN: 87 10895 97055 6
- Quantity: 4
- Gross weight: 4.31 kg
- Tare weight: 1.87 kg
- Net weight: 2.44 kg
- Length: 370 mm
- Width: 300 mm
- Height: 230 mm

SWV5530/I0

Product highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

4-Cut connectors

4-Cut connectors ensure secure connections between your component and your cable.

100% aluminium shielding

This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

Twisted high-purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Braided shielding

Copper-braided reinforced aluminium shielding protects against signal loss and interference.

FPE Dielectric

Foam Polyethylene (FPE) dielectric is a superior insulation material that protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2008-12-17

Version: 2.0.4

12 NC: 9082 100 06352
EAN: 87 10895 93456 5

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com