



HP One-view Perforated Adhesive Window Vinyl produces stunning, durable see-through window graphics full of vibrant colour and fine detail. It comes with permanent, clear self adhesive that removes cleanly without glue residue – even after 6 months.

Ideal for Print Service Providers wanting to diversify their business with high-quality, durable window graphics applications using HP Latex, low-solvent, solvent and UV-curable ink based printers.

Stop traffic with bold graphics full of vibrant colour and fine text and detail, ideal for viewing up close. Print with HP One-view Perforated Adhesive Window Vinyl and get high-impact graphics on the front, clear visibility from the back.

Enjoy the ease of working with this vinyl polymeric substrate. The permanent, clear self-adhesive removes cleanly, even after 6 months. This trouble-free solution helps save time and money.

Count on lasting results – prints achieve up to 1 year outdoor display permanence, unlaminated¹. Maintain an efficient workflow with this high-performance and fire resistant (M1) substrate².

¹Image permanence and water-resistance ratings by HP Image Permanence Lab
Outdoor display permanence tested according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change
For more information, see www.hp.com/go/supplies/printpermanence

²Meets the following fire-resistant ratings: M1 / NFP 92-501 (France).

HP One-view Perforated Adhesive Window Vinyl

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	288 g/m ² (with liner), 155 g/m ² (without liner) per ISO 536 Test Method		
Thickness	16 mil/406 microns (with liner), 6.5 mil/165 microns (without liner) per ISO 534 Test Method		
Opacity	98% (with liner) per TAPPI T-425 Test Method; 75% (with liner) per TAPPI T-426 Test Method		
Lamination	Yes, with laminates designed for perforated vinyl		
Finish	Semi-gloss		
Adhesive backing	Clear		
Operating temperature	15 to 30° C		
Operating humidity	30 to 70% RH		
Lightfastness (Indoor Commercial Window)	1 year. For details: http://www.hp.com/go/supplies/printpermanence .		
Low-solvent Ink			
Lightfastness (Indoor Home or Office)	1 year. For details: http://www.hp.com/go/supplies/printpermanence .		
Low-solvent Ink			
Flame Retardant	No		
Waterfastness	Yes		
Shelf time	1 year, unopened in original packaging		
Storage temperature	18 to 30° C		
Storage humidity	35 to 55% RH		
Country of origin	Product of Taiwan		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CH004A	1067 mm x 50 m	884962282878
	CH005A	1372 mm x 50 m	884962282885
Warranty	Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly.		

© 2009 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-9434 EEE

