



HP White Satin Poster Paper produces durable prints with rich detail and brilliant colour that grabs attention indoors and outdoors. Versatility across inks helps you offer new applications.

Ideal for print service providers looking for a competitively priced, reliable substrate compatible across HP Latex, low-solvent, solvent, and UV-curable inks and ideal for short-run indoor/outdoor advertising campaigns and billboard applications.

Offer indoor and outdoor campaigns produced on HP White Satin Poster Paper, manufactured according to ISO 14001, the voluntary international standard for environmental management systems.

Scratch-resistant prints dry quickly and stay intact after folding. Use water-resistant prints outdoors, without lamination¹. HP White Satin Poster Paper delivers the easy, trouble-free printing you expect from HP.

Get attention-grabbing, vibrant colour, high-definition sharpness and brilliant colour saturation for indoor and outdoor campaigns, including billboards. Expand your applications with versatile HP White Satin Poster Paper.

¹ Image permanence and water-resistance ratings by HP Image Permanence Lab
Outdoor display permanence tested according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change
For more information, see www.hp.com/go/supplies/printpermanence.

HP White Satin Poster Paper

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	136 g/m² per ISO 536 Test Method		
Thickness	6.5 mil/165 microns per ISO 534 Test Method		
Opacity	95% per TAPPI T-425 Test Method		
Whiteness	110 per CIE Ganz 82 Test Method		
Lamination	Yes, hot and cold		
Finish	Satin		
Operating temperature	15 to 30° C		
Operating humidity	30 to 70% RH		
Lightfastness (Archivability) Low-solvent Ink	In test		
Lightfastness (Indoor Commercial Window) Low-solvent Ink	In test		
Lightfastness (Indoor Home or Office) Low-solvent Ink	In test		
Flame Retardant	No		
Waterfastness	Yes		
Shelf time	1 year, unopened in original packaging		
Storage temperature	18 to 30° C		
Storage humidity	35 to 55% RH		
Country of origin	Product of Germany		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CH001A	1372 mm x 61 m	884962282847
	CH002A	1524 mm x 61 m	884962282854
	CH010A	1067 mm x 61 m	884962372609
Warranty	Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly.		

© 2009 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-9432 EEE

