



HP Backlit Scrim Banner is a competitively priced, durable backlit scrim banner for a wide range of outdoor uses. The low opacity distributes light evenly for maximum impact and exceptional image quality.

Ideal for Mid-volume print service providers (PSPs) looking for a Backlit Scrim Banner compatible with HP Latex and low-solvent inks.

This tear-resistant media made to withstand the wind and rain, and serves a full range of indoor and outdoor applications. Its construction is durable without sacrificing handleability or translucence.

This low-opacity backlit scrim banner ensures even light distribution and is just as impactful during the day when it is not being backlit.

Versatile enough for indoor or outdoor uses. Its tear- and wind-resistance makes it last outside, and its fire-resistant (B1) material is safe for indoor applications¹. Get a cost-effective solution that eliminates the need for post-processing.

¹ Meets the following fire-resistant ratings: B1 / DIN 4102 (Germany)

HP Backlit Scrim Banner

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	615 g/m² per ISO 536 Test Method		
Thickness	17.1 mil/435 microns per ISO 534 Test Method		
Opacity	90.5% per ISO 2471 Test Method		
Lamination	Lacqering possible		
Finish	High-gloss		
Tear resistant	>65N (MD) / >55N (CD) per ASTM D1004 Test Method		
Tensile strength	>1600 N/50mm (MD) / >1350 N/50mm (CD) per TAPPI T-494 Test Method		
Operating temperature	15 to 35° C		
Operating humidity	30 to 80% RH		
Lightfastness (Indoor Commercial Window) Low-solvent Ink	Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence .		
Flame Retardant	Yes, B1 / DIN 4102 (Germany)		
Waterfastness	Water-resistant		
Dry time	Less than 12 minutes with HP Designjet 9000 Printer series (@ 23°C, 50% RH) external dryer usage recommended		
Shelf time	1 year, unopened in original packaging		
Storage temperature	0 to 40° C		
Storage humidity	5 to 95% RH		
Country of origin	Product of China		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CG448A	1067 mm x 25 m	883585620166
	CG449A	1372 mm x 25 m	883585620173
	CG450A	1550 mm x 25 m	883585620180
	CG451A	2640 mm x 50 m	883585620197
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2008 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-1588 EEE

