

KVR333SO/512R

512MB 64M x 64-Bit DDR333

CL2.5 200-Pin SODIMM

DESCRIPTION:

This document describes ValueRAM's 64M x 64-bit (512MB) DDR333 CL2.5 SDRAM (Synchronous DRAM) memory module. The components on this module include sixteen 32M x 8-bit (8M x 8-bit x 4 Bank) DDR333 SDRAM sealed in FBGA packages. This 200-pin DIMM uses gold contact fingers and requires +2.5V. The electrical and mechanical specifications are as follows:

FEATURES:

- | | |
|---------------------------------|-------------------------------|
| ✓ Clock Cycle Time (tCK) | 6ns (min.) / 12ns (max.) |
| ✓ Row Cycle Time (tRC) | 60ns (min.) |
| ✓ Refresh Row Cycle Time (tRFC) | 72ns (min.) |
| ✓ Row Active Time (tRAS) | 42ns (min.) / 70,000ns (max.) |
| ✓ Single Power Supply of | +2.5V (+/- .2V) |
| ✓ Operating (IDD0) | 3.525 W |
| ✓ UL Rating | 94 V - 0 |

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.250" (31.75mm).




Figure 1: KVR333SO/512R 200-Pin SODIMM