

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Brand	CANDY
Short Description	CMDG 919 X
Annual Energy Consumption, AEC_{hood} (kWh/a)	121.5
Energy Efficiency class (2010/30/EC)	D
Energy Efficiency Index, EEI	97,4
Fluid Dynamic Efficiency (FDE_{hood})	13,1
Fluid Dynamic Efficiency class	D
Lighting Efficiency (LE_{hood})	6.4
Lighting Efficiency class	F
Grease Filtering Efficiency	83.3
Grease Filtering Efficiency class	C
Air flow at Min/Max speed in normal use, Q_{min}/Q_{max} (m³/h)	388,5/545
Air flow at at intensive or boost setting (m³/h)	NO
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	62/68
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	NO
Power consumption in off mode (P_o) (W)	0.38
Power consumption in standby mode (P_s) (W)	0
Time increase factor, f	-
Measured air flow rate at best efficiency point, QBEP (m³/h)	295.3
Measured air pressure at best efficiency point, PBEP (Pa)	265

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Measured electric power input at best efficiency point, WBEP (W)	165.6
---	--------------

Nominal power of the lighting system, WL (W)	40
---	-----------

Average illumination of the lighting system on the cooking surface, E_{middle} (lux)	255
---	------------