



HP Clear Gloss Cast Overlamine is the solution that lasts. Your prints will withstand the demanding conditions of outdoor display, from weather to cleaning, and the HP Performance Warranty covers you up to 5 years¹.

Ideal for customers using HP Air Release Adhesive Gloss Cast Vinyl, HP Clear Gloss Cast Overlamine provides protection from UV radiation, enhances the durability of the underlying graphics and enables maximum flexibility.

Durable, long-term applications—like vehicle wraps—are built to last. HP Clear Gloss Cast Overlamine provides protection from UV radiation, enhances the durability of the underlying graphics and enables maximum flexibility.

When you use HP Clear Gloss Cast Overlamine, your prints withstand the demanding conditions of outdoor display from weather to cleaning and the HP Performance Warranty covers image performance, durability, and clean removal up to 5 years².

Use HP Clear Gloss Cast Overlamine together with HP Air Release Adhesive Gloss Cast Vinyl. Air release channels make installation easy and prints leave behind little glue residue, so removal is clean and easy, even after 5 years.

¹When used with HP Air Release Adhesive Gloss Cast Vinyl, this solution comes with a new HP Performance Warranty. Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl.

²When used with HP Air Release Adhesive Gloss Cast Vinyl, this solution comes with a new HP Performance Warranty. Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl.

HP Clear Gloss Cast Overlamine

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	275 g/m ² per ISO 536 Test Method		
Thickness	3.2 mil/81.3 microns per ISO 534 Test Method		
Lamination	Yes (cold)		
Finish	Gloss		
Tensile strength	65.6 per ISO 1421 Test Method		
Adhesive backing	Acrylic adhesive		
Flame Retardant	No		
Waterfastness	Yes		
Shelf time	2 years, unopened in original packaging		
Storage temperature	10 to 35° C		
Storage humidity	30 to 70% RH		
Country of origin	Product of USA		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CH036A	1524 mm x 45.7 m	884962549292
	CH037A	1372 mm x 45.7 m	884962549308
	CH038A	1372 mm x 91.4 m	884962549315
Warranty	Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly.		

© 2009 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA0-1862 EEE

