

FSW-1650 Versione H/w: 6



Switch Fast Ethernet 16-porte

Product OverviewThe FSW-1650 switch provides an ideal solution for small businesses that demand a reliable network switch that provides a high bandwidth interface between file servers and workgroups, departments and offices.

Advanced Networking FeaturesThe LevelOne FSW-1650 is a wire-speed, nonblocking 16 port Fast Ethernet Unmanaged Switch with an internal power supply. It provides a network with an 8K MAC address table, 3.2Gbps backplane throughput, asymmetrical flow-control support for full-duplex network connectivity, auto-negotiation and Auto-MDIX. The 16-port Fast Ethernet Switch utilizes packetstore- and forwarding switching for error-free data transmissions and IEEE802.3x backpressure flow control to control data flow between the sending and receiving nodes as well as to prevent any data packet loss.

Compact DesignThe FSW-1650 is a compact designed network switch. Users can place the switch on any desktop area or mount it in a 19-inch server rack or cabinet by using the included rack-mounting accessory kit.

Quick Configuration and Easy MaintenanceThe LevelOne FSW-1650 does not require any software configuration. It is Plug-and-Play enabled for quick set-up and immediate use within the Local Area Network. The 16 port Faster Ethernet Switch is equipped with a full range of LEDs for instant error detection, networking monitoring and networktroubleshooting.

Caratteristiche

- Fornisce la flessibilità di 16 porte 10/100BASE-TX
- 10/100Mbps-Full/Half-duplex, Negoziazione automatica, Auto-MDI/MDIX
- Supporta 8.000 indirizzi MAC auto-learning e auto-aging
- Il controllo del flusso IEEE 802.3x protegge dalla perdita di pacchetti per la trasmissione affidabile dei dati
- Minimizza l'impronta di carbonio con tecnologie avanzate ad alta efficienza energetica (IEEE 802.3az)

Specifications

System Specifications

Standards:

IEEE 802.3i

IEEE 802.3u

IEEE802.3x

IEEE802.3az

Memoria Buffer:

2MB

Porta:

half Shielded

Indicatore:

Power, LINK/ACT

**Metodo trasmissione:**

Store- forward

Potenza Ingresso:

100-240V/AC

Consumo Energia:

2.75W

Backplane (Gbps):

3.2Gbps

Tabella Indirizzi MAC:

8K

Temperatura di esercizio (° C):

0°C~45°C

Umidità operativa (senza condensa):

10%~90%

Temperatura di conservazione (° C):

-40°C~70°C

Umidità di stoccaggio (senza condensa):

5%~90%

Features

Generale:

16port10/100Mbps

Performance

Velocità di inoltro del pacchetto:

148800pps

Jumbo Frame (K):

2KB

Physical Specifications

Dimensioni (L x P x A mm):

440x140x44mm

Peso (g):

1.6kg

Order Information

FSW-1650

Package Contents

FSW-1650

Kit Montaggio Rack 19"

Cavo di Alimentazione

Manuale d'installazione rapida

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.