



Philips

Multimedia Speakers 2.0

- Silk dome tweeter
- 3" Driver
- Headphone out, Audio-in
- 110 W, Bass radiator

SPA8210/12

PC speaker with high-fidelity sound

Obsessed with sound

Packing a powerful wOOx bass and a high-definition silk dome tweeter in a stylish aluminium-fronted cabinet, Philips SPA8210/12 speakers look and sound just wonderful!

Benefits

Rich, complex sound

- Dumbbell speaker design for naturally balanced sound
- 40 W RMS total output power
- Silk dome tweeter for crystal clear sound
- wOOx technology for rich yet precise bass without distortion
- PP driver material
- Well damped driver reduces vibration and sound distortion
- Distortion-free at maximum sound output

Exquisite design and finishing

- Aluminium metal front

Simplicity

- Compatible with any media
- Convenient aux-in and headphone out on front of speaker

PHILIPS

Features

Dumbbell speaker design




With a dumbbell speaker design, the high-range tweeter is positioned at the midpoint, between two lower frequency woofers. In this product the woofer driver is on top, with the tweeter in the middle and the Philips patented wOOx on the bottom. This configuration generates a more balanced sound making the overall audio effect more natural. And the premium finish of this quality speaker will complement you and your choice of audio equipment.

Aluminium metal front

Premium build quality design. The speaker's front is made from a single piece of anodised brushed aluminium – the same material used to build aircraft. The aluminium, curved to create an ideal acoustic chamber, optimises audio delivery for sound that is accurate, powerful, natural and crystal clear.

Silk dome tweeter



A silk dome tweeter holds a diaphragm made with silk—a superior material to that used in ordinary tweeters. The silk material used in the diaphragm has superior sound damping characteristics and its soft texture ensures minimal acoustic breakup. As a result, the sound produced by a silk dome tweeter is smooth, warm and has a wide range.

wOOx technology



wOOx technology is a revolutionary loudspeaker concept that allows you to hear and feel profoundly deep bass that is richer than any other audio system. Special speaker drivers work in harmony with the wOOx bass radiator, and precise tuning between the main driver and the tweeter ensures smooth transitions from low-mid to high frequencies. Dual suspension and a totally symmetrical sandwich construction deliver low and precise base without noticeable distortion. wOOx produces exceptionally deep and dynamic bass by using the speaker box full volume to truly magnify the impact of the music.

PP driver material

The polypropylene (PP) material in the driver, which is soft, makes for better high frequency sounds. It can help rolling out and produces a purer sound with better clarity and balance. Easier to integrate with the tweeter, the use of this lightweight material results in less vibration.

AUX-in and headphone out



Now you can enjoy your favourite music and entertainment even easier and more conveniently, via the aux-in and headphone out jack on the front of these speakers. Usually, if you want to connect another device other than your PC you have to unplug the 3.5 mm jack from the computer and that is not always expedient. But with the aux-in and headphone out connections on front you can quickly and easily listen to music straight from almost any device.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Audio systems

Output power in total	40 W
Power	100-240 V, 50/60 Hz
Frequency range	20 Hz-20 kHz
Input impedance	47 kOhm
Signal/Noise ratio	>75 dB
THD	<1%

Audio systems L/R channels

Rated output power	20 W x2
Audio power amplifier	Class-AB Amplifier
Channel separation	>45 dB
Input sensitivity	600 mV

Left/Right speakers

Speaker driver	3" full range, 20 mm silk dome
----------------	--------------------------------

Driver power range 1-20 W x2
Frequency range 60 Hz-20 kHz
Nominal impedance 8 ohm
Sensitivity 84 dB(2.83 V/1 m)

Connectivity

Cable length 1.5 m
Connector 3.5 mm stereo

Packaging content

Quick installation guide Yes
Number of satellites 2

Product dimensions

Depth 13 cm
Height 25.2 cm
Weight 1.79 kg
Width 20.2 cm

Packaging dimensions

Height 30.80 cm
Width 23.40 cm
Depth 15.20 cm
Net weight 2.05 kg
Gross weight 2.40 kg
EAN 08712581639839
Number of products included 1
Country of origin CN

Harmonised Systems Code 851822

Outer Carton

Length 31.20 cm
Width 24.20 cm
Height 31.50 cm
Gross weight 5.00 kg
EAN 18712581639836
Number of consumer packages 2

Loading Unit

Number of consumer packages 80
Length 113.60 cm
Width 73.20 cm
Height 126.20 cm
Gross weight 166.00 kg
Net weight 164.00 kg
GTIN/EAN 68712581639831
Type 8845
Number of CTIs per stack layer 20
Number of stack layers per unit 4
Number of outer cartons per layer 10



data subject to change
2016, April 21

Version: 5.0.9
EAN: 08712581639839

© 2016 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com