

KVR1066D3Q4R7SK2/16G

16GB (8GB 1024M x 72-Bit x 2 pcs.) PC3-8500

CL7 Registered w/Parity 240-Pin DIMM Kit

DESCRIPTION:

ValueRAM's KVR1066D3Q4R7SK2/16G is a kit of two 1024M x 72-bit 8GB (8192MB) DDR3-1066 CL7 SDRAM (Synchronous DRAM) registered w/parity, quad-rank memory modules. Total kit capacity is 16GB. Each module is based on thirty-six 256M x 4-Bit SDRAM internally stacked in eighteen DDP 512M x 4-Bit DDR3-1066 FBGA packages. The SPDs are programmed to JEDEC standard latency 1066Mhz timing of 7-7-7 at 1.5V. Each 240-pin DIMM uses gold contact fingers and requires +1.5V. The electrical and mechanical specifications are as follows:

FEATURES:


- ✓ JEDEC standard 1.5V $\pm$ 0.075V Power Supply
- ✓ VDDQ = 1.5V $\pm$ 0.075V
- ✓ 533MHz fCK for 1066Mb/sec/pin
- ✓ 8 independent internal bank
- ✓ Programmable CAS Latency: 6,7,8
- ✓ Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- ✓ Programmable CAS Write Latency(CWL) = 6(DDR3-1066)
- ✓ 8-bit pre-fetch
- ✓ Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- ✓ Bi-directional Differential Data Strobe
- ✓ Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm $\pm$ 1%)
- ✓ On Die Termination using ODT pin
- ✓ On-DIMM thermal sensor (Grade B)
- ✓ Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- ✓ Asynchronous Reset
- ✓ PCB : Height 30.50mm, double sided component, w/ Full DIMM Heat Spreader

PERFORMANCE:

- | | |
|--|--------------------------------|
| ✓ CL(IDD) | 7 cycles |
| ✓ Row Cycle Time (tRCmin) | 50.63ns (min.) |
| ✓ Refresh to Active/Refresh Command Time (tRFCmin) | 110ns (min.) |
| ✓ Row Active Time (tRASmin) | 37.5ns (min.) |
| ✓ Power | 6.510 W (operating per module) |
| ✓ UL Rating | 94 V - 0 |

MODULE DIMENSIONS:

Front side



Back side

