

VE200

Audio/Video Extender Extends Your Display 200 meters

The VE200 Audio/Video Extender System allows you to extend the distance between the computer system unit and the display monitor by up to 200m/500ft for video resolutions of 1280 x 1024 @ 60Hz. It accomplishes this by means of a local transmitting unit (VE200L), and a remote receiving unit (VE200R), connected by Cat 5e twisted pair cable.

The VE200 Audio/Video Extender System is ideal for installations where the display needs to reside in public view, but the system equipment can be safely tucked away. The Extender System is also useful for control and security purposes, where you can have the system unit in a secure area while the display is located in an area that is convenient for viewing.

Other useful applications for the VE200 Audio/Video Extender System include:

- Finance: The remote display of stock market information.
- Education: The remote display of lectures and lessons to lecture halls and classrooms.
- Business: The remote display of addresses to overflow rooms; video conferencing; and demos.




IR Remote Control Included

Features

- Uses Cat 5e cable to connect the local and the remote units
- Dual Audio/video
- Supports one local and two remote displays
- Transmission distance up to 200 m*
- High-quality video – up to 1920x1200@60Hz at 30m, 1600x1200@60Hz at 150m, 1280x1024@60Hz at 200m
- Audio and serial enabled
- Two gain control modes for sharpest picture quality
- Video gain and compensation adjustable via OSD
- IR receiver for quick and easy video quality adjustment
- IR remote control for screen on/off and video adjustment at remote site
- Provides a RS-232 channels for selection**
- Follows VESA FDMI mount standard
- Supports DDC for the local monitor
- Supports VGA, SVGA, XGA, SXGA, UXGA, WUXGA and multisync monitors

* 1. When combined in an installation with ATEN's VB552 (VGA Over Cat5 Repeater + Audio) can extend distance up to 450 m
2. VE200R can also be combined in an installation with the ATEN's Media Distribution Solution. For further details, please go to our website www.aten.com

** Only one RS-232 channel can be selected at a time.



Specification

Function	VE200L	VE200R
Connectors	Video In	1 x HDB-15 Male (Blue)
	Video Out	1 x HDB-15 Female (Blue)
	Audio In	1 x Mini Stereo Jack Female (Green)
	Audio Out	1 x Mini Stereo Jack Female (Green)
	RS-232	1 x DB-9 Female (Black)
	IR Jack	1 x DB-9 Male (Black)
	Unit to Unit	1 x RJ-45 Female
Switches	Local RS-232 Port	1 x Pushbutton
	Video Adjustment	N/A
	Power	1 (Orange)
LEDs	RS-232 Port	1 (Green)
	On Line	N/A
	On Line	1 (Green)
Video	1920x1200@60Hz at 30m, 1600x1200@60Hz at 150m, 1280x1024@60Hz at 200m	
Cable Distance	200 m	
Power Consumption	DC 5.3V, 2W	DC 5.3V, 3.9W
Environment	Operating Temp.	0-50°C
	Storage Temp.	-20-60°C
	Humidity	0-80% RH, Non-condensing
Physical Properties	Housing	Metal
	Weight	0.34 kg
	Dimensions (L x W x H)	13.90 x 8.80 x 2.86 cm

* The specifications and pictures are subject to change without notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Printed 05/2014 V7.0



© Copyright 2014 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.