

## KVR1066D3S8R7S/1G

1GB 128M x 72-Bit PC3-8500

CL7 Registered w/Parity 240-Pin DIMM

### DESCRIPTION

This document describes ValueRAM's 128M x 72-bit 1GB (1024MB) DDR3-1066 CL7 SDRAM (Synchronous DRAM) registered w/parity, single-rank memory module, based on nine 128M x 8-bit DDR3-1066 FBGA components. The SPD is programmed to JEDEC standard latency 1066Mhz timing of 7-7-7 at 1.5V. This 240-pin DIMM uses gold contact fingers and requires +1.5V. The electrical and mechanical specifications are as follows:


### FEATURES

- JEDEC standard 1.5V  $\pm$  0.075V Power Supply
- VDDQ = 1.5V  $\pm$  0.075V
- 533MHz fCK for 1066Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 6,7,8,9,10
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 7(DDR3-1066)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm  $\pm$  1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower than TCASE 85°C, 3.9us at 85°C < TCASE  $\leq$  95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component

### SPECIFICATIONS

|                                                  |                     |
|--------------------------------------------------|---------------------|
| CL(IDD)                                          | 7 cycles            |
| Row Cycle Time (tRCmin)                          | 50.625ns (min.)     |
| Refresh to Active/Refresh Command Time (tRFCmin) | 110ns (min.)        |
| Row Active Time (tRASmin)                        | 37.5ns (min.)       |
| Power                                            | 2.452 W (operating) |
| UL Rating                                        | 94 V - 0            |
| Operating Temperature                            | 0° C to 85° C       |
| Storage Temperature                              | -55° C to +100° C   |

Continued >>

**MODULE DIMENSIONS:**

(units = millimeters)

