


LTR	REV.	DESCRIPTION	DATE



NOTE:

1. CABLE:

UL2725 80°C 30V [26AWG(1/0.404)*2F
+AL/MY+DRAIN WIRE(1/0.32)*2]TIN
INS: FOAM-PE OD: $\phi 1.1 \pm 0.05$ mm
PVC JACKET OD: $\phi (2.2 \pm 0.1) * (7.8 \pm 0.2)$ mm COLOR: RED (PANTONE 200C)
PRINT: 2725 E209329 RJ AWM 80°C 30V VW-1 Serial ATA 26AWG LIAN FENG (BLACK WORD)
IMPEDANCE: 100 $\pm$ 5 OHM (SUPPLIER: LIAN FENG)

2. CONNECTOR:

2-1 MATERIAL:

HOUSING: HIGH TEMPERATURE POLYESTER & GLASS FIBER UL 94V-0
TERMINAL: COPPER ALLOY

2-1 PLATING:


CONTACT AREA: 15u" GOLD PLATED

3. HOOD: MOLDED TYPE, PVC 45P, COLOR: BLACK(NK-K01)

4. CABLE ASS'Y ELECTRICAL TEST:

- 4-1 100% OPEN SHORT & MIS WIRE TEST
- 4-2 CONTACT RESISTANCE 2 OHM MAX
- 4-3 INSULATION RESISTANCE 20M OHM MIN

5. PACKING: EACH PC / POLYBAG



Tolerance	Inch	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

Draw

Check

Engr



SERIAL ATA SIGNAL CABLE

www.equip-info.net

140-0723-1	500	10
DWG	L (mm)	T (mm)