

# HP Artist Matte Canvas 380 g/m<sup>2</sup>



**HP Artist Matte Canvas is ideal for printing high-quality, fine art reproductions and photographs at an affordable price. This mid-grade artist canvas features a bright-white coating and matte finish.**

- HP Artist Matte Canvas has a bright-white, matte finish, delivering artistic prints with outstanding image quality and precise colour at an affordable price.
- HP Artist Matte Canvas offers outstanding performance with impressive durability, handling and water-resistance.
- Long-lasting prints and excellent image stability when used with HP Vivera pigment inks.

Ideal for fine artists, professional photographers, art reproduction houses and graphics-oriented print service providers seeking an affordable, high-quality medium.

# HP Artist Matte Canvas 380 g/m<sup>2</sup>

## Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

For the latest ICC/media profiles, please visit [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies) (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

|                       |                                                                                                                                                                                                                                                                              |                  |                 |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|
| Weight                | 380 g/m² per ISO 536 Test Method                                                                                                                                                                                                                                             |                  |                 |
| Thickness             | 18 mil/457 microns per ISO 534 Test Method                                                                                                                                                                                                                                   |                  |                 |
| Opacity               | Greater than 98% per TAPPI T-425 Test Method                                                                                                                                                                                                                                 |                  |                 |
| Brightness            | 92% per TAPPI T-452 Test Method                                                                                                                                                                                                                                              |                  |                 |
| Whiteness             | 120 per CIE Ganz 82 Test Method                                                                                                                                                                                                                                              |                  |                 |
| Lamination            | Yes (Liquid; water-based laminates)                                                                                                                                                                                                                                          |                  |                 |
| Mounting              | Glue-down mounting to MDF using Maxit by Daige                                                                                                                                                                                                                               |                  |                 |
| Finish                | Matte                                                                                                                                                                                                                                                                        |                  |                 |
| Operating temperature | 15 to 30° C                                                                                                                                                                                                                                                                  |                  |                 |
| Operating humidity    | 30 to 70% RH                                                                                                                                                                                                                                                                 |                  |                 |
| Waterfastness         | This product is water resistant when using HP pigment inks                                                                                                                                                                                                                   |                  |                 |
| Dry time              | Quick-dry (to touch) @ 23°C, 50% RH                                                                                                                                                                                                                                          |                  |                 |
| Shelf time            | 1 year, unopened in original packaging                                                                                                                                                                                                                                       |                  |                 |
| Storage temperature   | 10 to 35° C                                                                                                                                                                                                                                                                  |                  |                 |
| Storage humidity      | 20 to 80% RH                                                                                                                                                                                                                                                                 |                  |                 |
| Country of origin     | Made in USA                                                                                                                                                                                                                                                                  |                  |                 |
| Ordering information  | Product Numbers                                                                                                                                                                                                                                                              | Roll sizes       | UPC codes       |
|                       | Q8704A                                                                                                                                                                                                                                                                       | 610 mm x 6.1 m   | 8 82780-49059 8 |
|                       | Q8705A                                                                                                                                                                                                                                                                       | 914 mm x 15.2 m  | 8 82780-49060 4 |
|                       | Q8706A                                                                                                                                                                                                                                                                       | 1067 mm x 15.2 m | 8 82780-49061 1 |
|                       | Q8707A                                                                                                                                                                                                                                                                       | 1524 mm x 15.2 m | 8 82780-49062 8 |
| Warranty              | HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller. |                  |                 |

© 2006 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit  
<http://www.hp.com/go/designjet/supplies>

Published in EMEA 12/2006 4AA0-6590 EEE

