

REDUNDANT

MRG-6500P // SLEEVED // 500WATT



Product: PSU

Form factor: PSII

Color: silver

If you look for a redundant PSU for your server, MRG-6500P will be your chosen for this purpose. It has the 1st-class quality, powerful and secure.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: < 80%

Dimensions (DxWxH): 210mm x 150 mm x 87 mm

PCF: Active PFC (0,9)

Fan: 40mm fan (2x 40mm per module)

Connectors

24 PIN	8PIN EPS	System LED	SATA	Molex	Floppy	TTL Signal Kabel	Buzzer
1	1 inkl. Adapter auf 6PIN PCIe + 4PIN12V	1	2	8	2	1	1

DC Output / AC Input

AC INPUT: 100V / 9A 240V / 4,5A FREQUENCY: 47 - 63 HZ MAX. LOAD: 500W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	-5V	P.F.	-12V	+5VSB
	35A	25A	32A	N/A	N/A	0,8A	>0,9	1A	2,5A
	48A max.		+5V, 3,3V, 12V1 combi. / 472W						

Security:

Met.al frame, 2x 320W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.