

PRG-UNV(-W)
PRG-1(-W)




Max load
50lb (22kg)

PRG Precision Gear Projector Mount

FOR MULTIMEDIA PROJECTORS UP TO 50LB (22KG)

Peerless-AV's PRG Precision Gear Projector Mount simplifies image alignment. The patent-pending precision gear design allows exact tilt and roll image positioning by either simply turning two adjustment knobs with a Phillips screw driver, or use the tool-less option by extending the knobs to adjust by hand. Just set the precision gear to the desired position to secure it in place – it will hold its position even during projector maintenance. With Peerless-AV's PRG Precision Gear Projector Mount, just set it and forget it. No more adjustment screws. No more micro adjustments. No more hassles.

- Patent-pending precision gears provide exact projector image alignment
- Two adjustment knobs control projector image alignment
- Pre-assembled design reduces installation time
- Horizontal wrench access slots make flush mounting installations fast and easy
- Cable management allows cables to be routed through the projector mount and out of sight
- "U" shaped pitch bracket allows for hassle free cable routing
- Quick-release mechanism to easily service projector
- Spider® Universal Adaptor Plate extends up to 17.63" (448 mm) to fit most projector models
- Pre-installed security screws provide optional tilt and roll lock to prevent tampering with adjustment knobs
- Specifications:
 - Tilt: $\pm 20^\circ$
 - Roll: $\pm 10^\circ$
 - Swivel: 360° when mounted on extension column
 $\pm 15^\circ$ when flush mounted on ceilings



Precision Gear Technology



"U" Shaped Pitch Bracket for Easy Cable Routing



Exclusive Horizontal Wrench Access Slot



RoHS
COMPLIANT

TAA
COMPLIANT

✉ info@peerless-av.com

🌐 peerless-av.com

peerless-AV®
Driving Technology Through Innovation

Model Numbers

WARRANTY: Limited 5-year

PRG-UNV(-W):	PRG Precision Projector Mount with Spider® Universal Adaptor Plate
PRG-1(-W):	PRG Precision Projector Mount (PAP Model Adaptor Plate Required)

Product Specifications


	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
PRG-UNV(-W)	8.5"-17.63" x 3.81"-4.81" x 8.5"-17.63" (216-448 x 97-122 x 216-448mm)	3.08lb (1.4kg)	50lb (22kg)	Scratch Resistant Fused Epoxy	PRG-UNV: Black PRG-UNV-W: White
PRG-1(-W)	5.58" x 2.47" x 5.58" (142 x 63 x 142mm)	1.56lb (.71kg)			PRG-1: Black PRG-1-W: White

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
PRG-UNV(-W)	6.19" x 2.81" x 11.63" (157 x 71 x 295mm)	3.78lb (1.7kg)	PRG-UNV: 735029249887 PRG-UNV-W: 735029249900	PRG Precision Gear Projector Mount, Spider® Universal Adaptor Plate, Mounting and Projector Attachment Hardware, Assembly Instructions	1
PRG-1(-W)	6.5" x 3" x 7.125" (165 x 76 x 181mm)	1.82lb (.83kg)	PRG-1: 735029249856 PRG-1-W: 735029249870	PRG Precision Gear Projector Mount, Mounting Attachment Hardware, Assembly Instructions	

Accessories

CMJ MODELS, ACC570, ACC571, ACC912:	Ceiling Kits	ACC830:	Side-to-Side Adjuster
ACC840/845:	Anit-Vibration Mount	PWA14 & EXA/B:	Wall Mount Arm
ADJ, EXT AND EXA/B/C:	Extension Columns	ACC050:	Stability Kit
ACC800/850 & ACC852/856:	Cable Management Adaptor		



Architect Specifications

The PRG-Precision Gear Projector Mount shall be a Peerless-AV model PRG-UNV or PRG-1 and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
2300 White Oak Circle
Aurora, IL 60502 USA
(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV EMEA
Unit 3 Watford Interchange
Colonial Way, Watford
Herts, WD24 4WP
United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV Latin America
Ave de las Industrias 413
Parque Industrial Escobedo
Escobedo, N.L.,
Mexico 66062
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

