



17-inch Modularized KVM Console



KVM-0217

H/W Version: 1

Product Overview

The LevelOne KVM-0217 is a compact and modular KVM console drawer designed to be used in a standard 19-inch server rack. It offers connectivity to 8 or 16 computers by depending on the LevelOne KVM module that is installed (KCM-0831 or 1631). It features a 17-inch retractable LCD monitor and keyboard with built-in touchpad. Users can daisy chain up to seven KVM-0217 together, providing control of up to 128 computers in total. The LevelOne KVM-0217 provides a double layer password access control ensuring only authorized users have access to connected computers.

It supports an administrator and 8 user accounts, each one with a separate and customizable profile.

Advanced Remote Management via optional modules

LevelOne also offers a unique module for remote server control. Just slide in the IP Console Module (ACC-2000) to KCM-0831/1631 to access and manage the server farm over the Internet using a standard web browser. It supports a 1600x1200 pixel screen resolution for high-quality viewing.



1. KCM Moudule Connector



Key Features

- Control servers and computers either locally via control port or remotely via optional modules through the module expansion slot
- Combo architecture with PC support for PS/2 and USB interface
- Flexible auto-scan mode for flexible PC monitoring
- Locate Cat5 console up to 300 meters away from the KVM switch.
- Built-in daisy chain port for cascading with KVM-0831 or KVM-1631 up to 8 units
- Provide ACL (Access Control List) security function - store up to 8 independent ACLs for controllable PCs
- Support Windows, NetWare, Unix, Linux, Mac OS and Sun Microsystems
- 19" rackmount 1U size design KVM (Keyboard, video and mouse) access over IP

Works Well With



KCM-0831
8-port Combo KVM Module
for KVM-0217



KCM-1631
8-port Combo KVM KVM
Module for KVM-0217

* Features are based on KVM-0217 combined a LevelOne KVM mobule.


Technical Specification

Switch Ports
PC Port
8-port HDDB15 for PS2/USB
Local Console Port
1 Console port for USB
1 Expansion Slot for optional modules
*ACC-1000 KVM Cat.5 Console Module
*ACC-2000 IP KVM Console Module
Keyboard and Mouse Emulation
PS/2 or USB
VGA Resolution
1920X1440
Daisy Chaining
Daisy Chaining
Support Daisy Chaining up to 8 units
Connector: HDDB 15 pin (Female Type)
Daisy Chain Max. Level
8 units
Max. PC Connection
120 PCs/Servers (cascading 1 KVM-0831 + 7 KVM-1631)
Scan Intervals
5 ~ 99 Sec.
Bandwidth
200 MHz
Switch Management
PC selection
On Screen Display (OSD) Menu, Hot Key, Push Button

Security
Provide ACL (Access Control List) security function, store up to 8 independent controllable PC lists
Hotkey
Provide various Hotkey (Scroll-Lock/ Cap-Lock/ Num-Lock/ Alt/ Ctrl/ Win)
Multilingual OSD (On Screen Display) control
8 languages (English, France, German, Spanish, Italian, Russian, Japanese, Simplified Chinese)
Physical Specifications
PC LEDs
8
Housing
Metal
Power Adapter
DC 12V, 4.16A
Operation Temperature
0 ~ 50°C
Storage Temperature
-20 ~ 60°C
Humidity
0~95%, Non-Condensing
Dimension (mm)
445 (L) x 160(W) x 45 (H)
2.0 kg

** Specifications are based on KVM-0217 + KVM-0831/1631 modules.

Product Diagram



Order Information

Package Contents

KVM-0217: 17-inch Modularized KVM Console

- KVM-0217 x 1
- Rail with front and rear bracket x 2
- Brackets A. (Needed for rack depth 828 ~ 1000 mm) x 2
- Brackets B. (Needed for rack depth 504 ~ 614 mm) x 2
- Brackets C. (Needed for rack depth 504 ~ 614 mm) x 2
- Power Adapter x 1
- CD Manual x 1
- QIG x 1
- Keys x 2
- Screws

Option Accessories



ACC-2109
Daisy Chain Cable 90cm



ACC-2101
PS/2 and USB Cable KVM
1.8m



ACC-2102
PS/2 and USB Cable KVM
3.0m



ACC-2103
PS/2 and USB Cable KVM
5.0m