



LevelOne ViewCon

LevelOne 4 Port KVM Switch with OSD for PS/2

LevelOne 4 Port KVM Switch with OSD for USB and PS/2

LevelOne 8 Port KVM Switch with OSD for PS/2

LevelOne 8 Port KVM Switch with OSD for USB and PS/2

LevelOne 16 Port KVM Switch with OSD for PS/2

LevelOne 16 Port KVM Switch with OSD for USB and PS/2



TECHNICAL DATA

Computer Port Number

- KVM-0410/KVM-0420: 4 Ports
- KVM-0810/KVM-0820: 8 Ports
- KVM-1610/KVM-1620: 16 Ports

Cascade Control PC Number

- KVM-0410 and KVM-0420: up to 16
- KVM-0810 and KVM-0820: up to 64
- KVM-1610 and KVM-1620: up to 136

Automatic Scan Interval

- 3, 8, 15, 30 Seconds

Security Control

- 14 Character Password per Computer

Maximum Cable Length

- 30m at Console, 30m at PC Port

Cable Type

- | | | | |
|------------------|----------|------|----------------|
| ▪ 1 to 2 (USB): | ACC-2003 | 1,8m | Cable for USB |
| | ACC-2004 | 3,0m | Cable for USB |
| ▪ 1 to 3 (PS/2): | ACC-2001 | 1,8m | Cable for PS/2 |
| | ACC-2002 | 3,0m | Cable for PS/2 |

Console Connector

- PS/2 Female for Keyboard x 1
- PS/2 Female for Mouse x 1
- HDB15 Female for Monitor x 1

PC Port Connector

- KVM-0410 and KVM-0420: HDB15 Male x 4
- KVM-0810 and KVM-0820: HDB15 Male x 8
- KVM-1610 and KVM-1620: HDB15 Male x 16

LEDs

- Green for Computer be ready
- Red for Computer be selected

Method of Switching PC Port

- Pushbuttons, Hot Key Control, On Screen Display (OSD)

VGA Bandwidth

- 1920 x 1440, DDC2B

Physical Characteristics

- Power: Internal Power Adapter with 12V DC, 500mA
- Dimensions: 404mm x 40mm x 114mm (W x H x D)
- Rack-Mounted: 1 U, 19" Industrial Standard

Regulation

- CE

Ordering Information

- | | |
|------------|--|
| ▪ KVM-0410 | 4 Port KVM Switch w. OSD for PS/2 |
| ▪ KVM-0420 | 4 Port KVM Switch w. OSD for USB and PS/2 |
| ▪ KVM-0810 | 8 Port KVM Switch w. OSD for PS/2 |
| ▪ KVM-0820 | 8 Port KVM Switch w. OSD for USB and PS/2 |
| ▪ KVM-1610 | 16 Port KVM Switch w. OSD for PS/2 |
| ▪ KVM-1620 | 16 Port KVM Switch w. OSD for USB and PS/2 |
| ▪ ACC-2001 | 1,8m Cable for PS/2 |
| ▪ ACC-2002 | 3,0m Cable for PS/2 |
| ▪ ACC-2003 | 1,8m Cable for USB |
| ▪ ACC-2004 | 3,0m Cable for USB |