

CS9134



- 4-Port PS/2 KVM Switch

→ CS9134 is a KVM Switch with built-in PS/2. It can control 4 servers via a single console and allows users to switch between computers via the buttons on the front panel of the switch or the hotkey configuration on the console keyboard. It is the simplest and most convenient most convenient solution for multi-computer management. Moreover, it supports 3-tier connection via cascade. With 21 sets of CS9134, users can control 64 computers.



Features

- One PS/2 console controls 4 computers.
- Cascadable up to 3 levels - provides up to 64 computers.
- Computer selection via front panel pushbuttons, hotkeys or On Screen Display (OSD).
- Keyboard and mouse emulation for error free booting.
- Supports Microsoft IntelliMouse, Logitech MouseMan, FirstMouse, IBM Scrollpoint Mouse.
- OSD automatically adjusts to resolution changes.
- Auto Scan function to monitor computer operation.
- Superior video quality: up to 1920 x 1440; DDC2B.
- Available in silver and black.
- Special design for easy stacking.
- Rack mountable in 19" (1U) system rack.
- Multiplatform support: Windows 2000/XP/[Vista](#), Linux and FreeBSD.
- For more information about KVMs which can connect to CS9134, see [Compatible KVM Table](#).

Specification

Computer Connections		Direct	4
		Max.	64 (via Cascade)
Port Selection			Hotkey, Pushbutton, OSD
Connectors	Console Ports	Keyboard	1 x 6-pin Mini-DIN Female (Purple)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x 6-pin Mini-DIN Female (Green)
	KVM Ports	Keyboard	4 x 6-pin Mini-DIN Female (Purple)
		Video	4 x HDB-15 Male (Blue)
		Mouse	4 x 6-pin Mini-DIN Female (Green)
	Power		1 x DC Jack (Black)
Switches	Power	4 x Pushbutton	
LEDs	On Line		4 (Green)
	Selected		4 (Orange)
	Power		1 (Blue)
Emulation	Keyboard		PS/2
	Mouse		
Video			1920 x 1440; DDC2B
Scan Interval			3,5,10,15,20,30,40,60 Seconds
Power Consumption			DC9V, 0.9W
Environment	Operating Temp.		0-50°C
	Storage Temp.		-20-60°C
	Humidity		0-80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight		2.55 kg
	Dimensions (L x W x H)		45.00 x 17.00 x 6.70 cm

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2012 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.