



HP Heavy Textile Banner is a woven polyester media with a smooth surface providing excellent handleability, image quality, and scratch- and tear-resistance. This fire-resistant (B1) media is certified for indoor use¹.

Ideal for mid-volume print service providers (PSP) looking for high-quality fabric banner compatible with HP Latex and HP low-solvent inks.

This easy-to-handle woven polyester banner can be draped indoors, used as an indoor/outdoor banner or as a window display. The smooth surface is stitchable and scratch-resistant.

A woven textile banner that is safe for indoor use and is tear- and scratch-resistant. This durable, easy-to-handle media saves time and money by reducing reprints. Saves post-processing time; doesn't require lamination for outdoor applications.

Fire certifications (B1) make this media a reliable choice for a multitude of indoor and outdoor applications. Extensive colour range and high whiteness provides an ideal canvas for an array of bright colours for enhanced impact and visibility.

¹ Meets the following fire-resistant ratings: B1 / DIN 4102 (Germany)

HP Heavy Textile Banner

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	280 g/m² per ISO 536 Test Method		
Thickness	15 mil/382 microns per ISO 534 Test Method		
Lamination	Lacquering possible		
Mounting	Grommet, sew, D-rings		
Finish	Matte		
Tear resistant	>110N (MD) / >90N (CD) per ASTM D1004 Test Method		
Tensile strength	>1100 N/50mm (MD) / >1400N/50mm (CD) per TAPPI T-494 Test Method		
Operating temperature	15 to 35° C		
Operating humidity	30 to 80% RH		
Lightfastness (Indoor Commercial Window) Low-solvent Ink	Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence .		
Flame Retardant	Yes, B1 / DIN 4102 (Germany)		
Waterfastness	Water-resistant		
Dry time	Less than 10 minutes with the HP Designjet 900 Printer series (@ 23°C, 50% RH)		
Shelf time	1 year, unopened in original packaging		
Storage temperature	5 to 40° C		
Storage humidity	5 to 95% RH		
Country of origin	Product of Germany		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CG435A	965 mm x 40 m	883585619924
	CG436A	1550 mm x 40 m	883585619931
	CG437A	2642 mm x 50 m	883585619948
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2008 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-1592 EEE

