

Micro HDMI or HDMI to VGA Adapter - 1920x1200

Product ID: MCHD2VGA



The MCHD2VGA HDMI / Micro HDMI to VGA Converter lets you connect an HDMI-enabled video source device to a VGA monitor or projector. The adapter also includes a Micro HDMI to HDMI adapter, for added compatibility with Micro HDMI tablets and smartphones - an ideal solution for sharing presentations or worksheets from your HDMI and Micro HDMI devices, on a classroom or boardroom projector.

The MCHD2VGA provides an active video connection making the MCHD2VGA the perfect solution for low-power HDMI sources, such as MacBook® and Mac Mini computers.

For added convenience, the adapter can be powered using any USB power source, even the computer or television the device is connected to. A power adapter is also included ensuring you can connect the adapter to a regular power outlet where a USB Power source may not be available.

Note: The adapter will not pass digitally encrypted content.

The MCHD2VGA is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Carry with your laptop, smartphone or tablet for BYOD applications with VGA displays
- Share presentations on a classroom or boardroom projector
- Connect the low-powered HDMI port on your Mac Mini or MacBook to a VGA projector
- Power using the USB port on your computer for added mobility and fast installation

Features

- Micro HDMI to HDMI adapter included, for added compatibility with Micro HDMI smartphones and tablets
- Active converter for low-powered HDMI source devices such as MacBook & Mac Mini
- Conveniently USB powered with included A.C outlet to USB adapter
- Supports video resolutions up to 1920 x 1200 / 1080p

Hardware	Warranty	3 Years
	Active or Passive Adapter	Active
	Audio	No
	AV Input	HDMI
	AV Output	VGA
	Industry Standards	High Speed HDMI®
	Ports	1
Performance	Supported Resolutions	1920x1200, 1920x1080 (1080p), 1600x1200 @ 60Hz
Connector(s)	Connector A	1 - HDMI (19 pin) Female Input
	Connector B	1 - VGA (15 pin, High Density D-Sub) Female Output
	Connector Type(s)	1 - USB Mini-B (5 pin) Female
Power	Input Voltage	100 ~ 240 AC
	Output Current	1 A
	Output Voltage	5 DC
	Plug Type	USB Mini-B (5 pin)
	Power Consumption (In Watts)	1.75
	Power Source	AC Adapter Included
Environmental	Operating Temperature	0°C to 45°C (32°F to 113°F)
	Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	Color	Black
	Enclosure Type	Plastic
	Product Height	0.6 in [14 mm]
	Product Length	2.5 in [64 mm]
	Product Weight	1.3 oz [38 g]
	Product Width	1.6 in [41 mm]
Packaging Information	Shipping (Package) Weight	10 oz [284 g]
What's in the Box	Included in Package	1 - HDMI® to VGA Adapter
		1 - HDMI® to HDMI Micro Cable
		1 - AC to USB Power Adapter (North American)

Product appearance and specifications are subject to change without notice.