



HP Photo-realistic Poster Paper is a recyclable, highly versatile, high-performance media, delivering high image quality for indoor applications¹. Maximise productivity thanks to the quick dry time and some water-resistance without lamination.

Ideal for mid-volume print service providers (PSPs) looking for an affordable photo-realistic poster paper.

HP Photo-realistic Poster Paper delivers quality that rivals prints made with photo-based papers, making it the ideal media for a wide range of graphic display applications. This media can be used for a variety of indoor print applications.

Features a fast dry time for easy post-print processing. HP Photo-realistic Poster Paper can be laminated, mounted and processed conventionally, and enables users to move greater volumes for better profit margins.

This paper-based media delivers vibrant, photo-realistic prints for high-impact displays anywhere, and is a great alternative to more costly photo media. It delivers top quality images comparable to indoor photo paper.

¹ Recycling opportunities for this product currently only available in limited areas. Customers should consult local recycling resources for recycling this product.

HP Photo-realistic Poster Paper

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	205 g/m² per ISO 536 Test Method		
Thickness	8.1 mil/205 microns per ISO 534 Test Method		
Opacity	98% per TAPPI T-425 Test Method		
Brightness	90% per TAPPI T-452 Test Method		
Whiteness	110 per CIE GANZ 82 Test Method		
Lamination	Yes, hot, cold, and hot press		
Finish	Semi-gloss		
Operating temperature	15 to 100° C		
Operating humidity	20 to 80% RH		
Lightfastness (Indoor Home or Office)	150 years (with HP Designjet L65500 Latex Inks). For details: http://www.hp.com/go/supplies/printpermanence .		
Low-solvent Ink			
Waterfastness	Water-resistant		
Dry time	Instant dry with heating (@ 23°C, 50% RH)		
Shelf time	2 years, unopened in original packaging		
Storage temperature	0 to 40° C		
Storage humidity	5 to 95% RH		
Country of origin	Product of United States		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CG419A	914 mm x 61 m	883585618606
	CG420A	1372 mm x 61 m	883585618613
	CG421A	1524 mm x 61 m	883585618620
	CG422A	2261 mm x 61 m	883585618637
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2008 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-1597 EEE

