

CE800B

USB KVM Extender (With USB Flash Storage Support)

The CE800B USB KVM Extender with on-board audio allows access to a computer system from a remote console (USB keyboard and mouse, monitor, stereo speakers, and microphone). It is perfect for factory and construction sites, or any type of installation where the console needs to be in a conveniently accessible location, but you want the system equipment to reside in a safe place – away from dust, dirt, and harsh environmental influences.

The CE800B has built-in USB ports that support USB Mass Storage compliant flash drives. The addition of a Type B USB port on the local unit means that the flash drive facility is fully supported in both PC-only and KVM switch installation.




CE800BL

Features

- Cat 5e cable to connect the Local and Remote Units –up to 250 m (825 ft) apart
- Dual console operation – control your system(s) from both the local and remote consoles
- Pushbutton selection of the active console
- Built-in USB port on both units supports external USB Mass Storage compliant flash drives for easy file sharing
- Special security feature requires login when mounting an external USB storage device on the remote unit
- Supports VGA, SVGA, and multisync monitors – local monitor supports DDC; DDC2; DDC2B
- High resolution video – up to 1920x1200@60Hz at 30m, 1600x1200@60Hz at 150m, 1024x768@60Hz at 250m
- Built-in 8KV/15KV ESD protection and 2KV surge protection
- Adjustable gain control – automatically and manually adjusts signal strength to compensate for distance
- Supports stereo speakers and stereo microphone
- Supports Microsoft Intellimouse and the scrolling wheel on most mice
- Upgradable firmware
- Built-in ASIC for greater reliability and compatibility
- Supports Wide Screen formats *

* The EDID data for a widescreen is sent from the local video output port. For widescreen modes and displays connect the monitor to the local video output port or use an ATEN EDID emulator.



Specification

Function		CE800BL	CE800BR
Computer Connections		1	N/A
Connectors	Console	Keyboard	1 x USB Type A Female (White)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White)
		Speakers	1 x Mini Stereo Jack (Green)
		Microphone	1 x Mini Stereo Jack (Pink)
	KVM Ports	Keyboard/ Video / Mouse	1 x SPHD-15 Female (Yellow)
		USB Port	1 x USB Type B (Female) 1 x USB Type A (Female)
		Speakers	1 x Mini Stereo Jack (Green)
		Microphone	1 x Mini Stereo Jack (Pink)
	F/W Upgrade		1 x 4-conductor 3.5 mm jack
Switches	Power	1 x DC Jack	
	Unit to Unit (Link)	1 x RJ-45	
	Operating Mode Selection	1 x Pushbutton	
	Picture Compensation	N/A	2 x Pushbutton
LEDs	Local	1 (Green)	N/A
	Remote	1 (Green)	1 (Green)
	Link	N/A	1 (Green)
	Compensation	N/A	1 (Orange)
Power Consumption		DC 5 V, 6 W	
Video		1920x1200@60Hz at 30m 1600x1200@60Hz at 150m 1024x768@60Hz at 250m	
Environment	Operating Temp.	0-50°C	
	Storage Temp.	-20-60°C	
	Humidity	0-80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	0.50 kg	0.49 kg
	Dimensions (L x W x H)	20.00x8.15x2.63cm	20.00x8.15x2.63cm

* The specifications and pictures are subject to change without notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Printed 09/2014 V4.0



© Copyright 2014 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.