ST660(P)



Mounting Pattern
824 x 405mm
(32.44" x 15.95")

Max Load
200lb
(91kg)

SMARTMOUNT®

Universal Tilt Wall Mount

FOR 39" TO 80" DISPLAYS*

The SmartMount® Universal Tilt Wall Mount series offers the most versatile installation features and mounting options. Horizontal and vertical adjustment abilities allow for post installation leveling and side-to-side positioning, making it easier than ever to find the perfect TV position. Lock the tilt angle at installation to prevent tampering or moving with the IncreLok™ tilt technology. Security screws provided in the ST660 models deter tampering and theft. The open wall plate design offers total wall access, increasing the electrical and cable management options. The display can now simply be installed by a single person with the Hook-and-Hang™ system. The Easy-Glide™ adaptors hook onto the wall plate for an overall quick, simple and secure installation.

- Universal mount fits displays with mounting patterns up to 824 x 405mm (32.44" W x 15.95" H) and accommodates up to 800 x 400mm VESA® patterns
- Adjustable 15° forward tilt and 5° backward tilt for finding the optimal viewing angle
- Easy-Grip™ ratcheting handle locks tilt angle into place
- Up to 0.25" (6mm) of vertical adjustment on each universal display adaptor bracket for post-installation leveling and height adjustment fine-tuning
- Horizontal display adjustment up to 8.00" (203mm) for centering display on wall
- Includes all necessary wall and display attachment hardware
- Integrated security options available
- Design is UL listed and tested to four times stated load capacity
- For mounts requiring theft resistant hardware, installed with security tool (included), please purchase ST660
- For mounts requiring standard hardware, installed with a Philips screwdriver, please purchase ST660P



HOOK-AND-HANG™ INSTALLATION
Display is easily installed by a single person

HORIZONTAL & VERTICAL ADJUSTMENT
Post-installation leveling and side-to-side adjustability features allow fine tuning of the mounted display for the perfect display positioning

INCRELOK™ TILT TECHNOLOGY
Lock the tilt angle in 5° increments for the perfect view and prevent tampering or undesired adjustment

EASY-GLIDE™ ADAPTORS
Hook onto the wall plate for quick, simple and secure installation

OPEN WALL PLATE
Allows total wall access, increasing electrical and cable management options

+15°/-5° of tilt for versatile viewing angles.

Comes in color packaging with included installation hardware and easy to follow instructions.

Please visit peerless-av.com/en-us/patents for patent information.

*This display size range is simply a guideline for product selection. Displays larger than the screen size range may still be compatible as long as they fall within the VESA® pattern and max weight of the Peerless-AV® product.

info@peerless-av.com
peerless-av.com

peerless-AV®
Driving Technology Through Innovation

Model Numbers

WARRANTY: Limited 5-year

ST660P	SmartMount® Universal Tilt Wall Mount for 39" to 80" Displays - Standard Models
ST660	SmartMount® Universal Tilt Wall Mount for 39" to 80" Displays - Security Models

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
ST660(P)	36.54" x 16.89" x 2.62"-5.40" (928 x 429 x 67-137mm)	8.70lb (3.95kg)	200lb (91kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
ST660(P)	36.41" x 2.95" x 10.71" (925 x 75 x 272mm)	11.00lb (4.99kg)	ST660: 735029235606 ST660P: 735029231875	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

ACC309:	Video Conference Shelf
ACC415:	4-pack Metal Stud Fastener Kit
ACC925:	Security Fasteners for V200x200 to V800x400 Mounts
ACC-M835:	Security Fast-Pack, M8x25 & M8x35
ACC-UCM:	Universal AV Component Mount
ACC-V600X:	600mm Extension for 400mm Adaptors
ACC-V900X:	600, 800 or 900mm Extension for 400mm Adaptors
ACC-WMVCS:	Video Conferencing Shelf
ACSBR1:	Universal Sound Bar Mounting Kit
ESHV models:	AV Wall Shelves
IBA4-W:	Easy Mount Recessed Low Voltage Cable Plate
IBA5-W:	Recessed Low Voltage Media Plate w/ Duplex Surge Protector
IB14X9-W:	14x9" In-Wall Box
IB14X9-AC-W:	14x9" In-Wall Box with Duplex Surge Protector
IB14X14-W:	14x14" In-Wall Box
IB14X14-AC-W:	14x14" In-Wall Box with Duplex Surge Protector

All dimensions = inch (mm)



WALL PLATE



ADAPTOR BRACKET



FRONT VIEW



SIDE VIEW
+15°/-5° TILT

Architect Specifications

The SmartMount® Tilt Wall Mount shall be a Peerless-AV model ST660(P) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit **peerless-av.com** to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
2300 White Oak Circle
Aurora, IL 60502 USA

(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV EMEA
Unit 3 Watford Interchange
Colonial Way, Watford
Herts, WD24 4WP
United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV Latin America
Av. de las Industrias 413
Parque Industrial Escobedo
General Escobedo, N.L.,
México, 66062
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

peerless-AV®
Driving Technology Through Innovation

LIT-0596 Rev.8

© 2021 Peerless Industries, Inc. Peerless-AV® and SmartMount® are registered trademarks of Peerless Industries, Inc. All rights reserved.